

INDUSTRIAL COMPONENT DATA

GE1250 LOVATO THREE-POLE SWITCH DISCONNECTOR, 1250A

Brand: LOVATO ELECTRIC | Manufacturer Part Number: GE1250



Manufacturer	LOVATO ELECTRIC
MPN / Reference	GE1250
Catalog number	10000
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-8A4A0DF793
Generated	2026-07-31

Product Overview

THREE-POLE SWITCH DISCONNECTOR, 1250A

3P SWITCH DISCONNECTOR

Three-pole switch disconnecter, 1250A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LOVATO ELECTRIC > Switch disconnectors - LOVATO ELECTRIC

Additional Product Information

GE1250

Three-pole switch disconnecter, 1250A

Technical specifications

Type of product:Switch disconnectorsNumber of poles:3Type of operating voltage:ACIEC Conventional free air thermal current Ith [A]:1250Type of installation:Screw on plateOrder code GE1250

Weight [g] 8920

Qty. per package 1

Multiple qty. of packs per order 1

Package dimensions [mm] 345X325X165

Volume [cm³] 18500.625

Bar code [EAN13] 8013975175750

HS Code 85365080

1059.79 £

ETIM for GE1250 Low-voltage industrial controls and switchgear (EC000216)

Feature Name

Feature Value

Device construction (EF008240)

Built-in device fixed built-in technique

Type of control element (EF006976)

Door coupling rotary drive

Type of electrical connection of main circuit (EF006819)

Bolt connection

Rated operating voltage (EF001435)

400 V

Version as reversing switch (EF009408)

No

Voltage release optional (EF007491)

No

Motor drive optional (EF007386)

No

Suitable for distribution board installation (EF007262)

No

Suitable for front mounting 4-hole (EF007247)

No

Version as maintenance-/service switch (EF006986)

Yes

Version as safety switch (EF006985)

No

Version as main switch (EF006981)

Yes

Version as emergency stop installation (EF006959)

No

Motor drive integrated (EF006697)

No

Interlockable (EF006281)

No

Rated permanent current at AC-23, 400 V (EF011777)

1000 A

Rated permanent current at AC-21, 400 V (EF009165)

1250 A

Max. rated operation voltage Ue AC (EF007355)

690 V

Rated short-time withstand current Icw (EF007050)

25 kA

Rated op...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / GE1250 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.