

INDUSTRIAL COMPONENT DATA

7GN1292U25 GN1292U25 LOVATO ROTARY CAM SWITCHES, GN SERIES, U25-U65 VERSION FRONT MOUNT WITH PADLOCK SYSTEM, ..

Brand: LOVATO ELECTRIC | Manufacturer Part Number: 7GN1292U25



Manufacturer	LOVATO ELECTRIC
MPN / Reference	7GN1292U25
Catalog number	GN1292U25
Category	Off-load switch
Minimum order	1 Pcs
Document ID	EO-23409EC872
Generated	2026-08-03

Product Overview

ROTARY CAM SWITCHES, GN SERIES, U25-U65 VERSION FRONT MOUNT WITH PADLOCK SYSTEM, RED/YELLOW. ON/OFF SWITCH, FOUR-POLE - 2 WAFERS - SCHEME 92, 16A

IIII GN92 16A Switch Mod. U25 65x65

Rotary cam switch 7GN series, ON-OFF switch 4 poles 16A, for front mounting with red/yellow handle padlockable in 0 and protection covers, front plate 65X65mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LOVATO ELECTRIC > Rotary cam switches - LOVATO ELECTRIC

Additional Product Information

7GN1292U25

Rotary cam switch 7GN series, ON-OFF switch 4 poles 16A, for front mounting with red/yellow handle padlockable in 0 and protection covers, front plate 65X65mm

Technical specifications

Type of product: ON/OFF switches Switching diagram: 92 - ON/OFF switch 4 poles IEC Conventional free air thermal current Ith [A]: 16 Mounting form: U25 - Front mounting with red/yellow handle padlockable in 0 and protection covers Series: 7GN - round-shaped contact block Order code 7GN1292U25

Weight [g] 161

Qty. per package 1

Multiple qty. of packs per order 1
Package dimensions [mm] 050X050X082
Volume [cm³] 205
Bar code [EAN13] 3850144003194
HS Code 85365080
33.31 £
ETIM for 7GN1292U25 Low-voltage industrial controls and switchgear (EC001105)
Feature Name
Feature Value
Type of control element (EF006976)
Short thumb-grip
Type of electrical connection of main circuit (EF006819)
Screw connection
Degree of protection (IP), front side (EF003118)
IP40
Housing material (EF001596)
Plastic
Model (EF000010)
On/Off switch
Complete device in housing (EF007317)
Yes
Suitable for intermediate mounting (EF007264)
No
Suitable for distribution board installation (EF007262)
Yes
Suitable for front mounting (EF007246)
Yes
Suitable for floor mounting (EF007243)
No
With retraction in 0-position (EF002428)
No
With zero (off) position (EF001416)
Yes
Number of poles (EF001391)
4
Rated permanent current I_u (EF001389)
16 A
Rated operation power at AC-3, 400 V (EF001364)
4 kW

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / 7GN1292U25 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.