

INDUSTRIAL COMPONENT DATA

7GN2592P25 GN2592P25 LOVATO ROTARY CAM SWITCH, GN SERIES, P25 VERSION IN ENCLOSURE WITH PADLOCKABLE ROTATING HANDLE..

Brand: LOVATO ELECTRIC | Manufacturer Part Number: 7GN2592P25



Manufacturer	LOVATO ELECTRIC
MPN / Reference	7GN2592P25
Catalog number	GN2592P25
Category	Off-load switch
Minimum order	1 Pcs
Document ID	EO-0F77FF1F83
Generated	2026-08-03

Product Overview

ROTARY CAM SWITCH, GN SERIES, P25 VERSION IN ENCLOSURE WITH PADLOCKABLE ROTATING HANDLE.

ON/OFF SWITCH, FOUR POLES - SCHEME 92, 25A

IIII GN92 25A Switch Mod. P25 90x90

Enclosed rotary cam switch 7GN series, ON-OFF switch 4 poles 25A in plastic enclosure 90X90mm with red/yellow handle

ENCLOSED ROTARY CAM SWITCH 7GN SERIES, ON-OFF SWITCH 4 POLES 25A IN PLASTIC ENCLOSURE 90X90MM WITH RED/YELLOW HANDLE

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LOVATO ELECTRIC > Rotary cam switches - LOVATO ELECTRIC

Additional Product Information

7GN2592P25

Enclosed rotary cam switch 7GN series, ON-OFF switch 4 poles 25A in plastic enclosure 90X90mm with red/yellow handle

Technical specifications

Type of product: ON/OFF switches Switching diagram: 92 - ON/OFF switch 4 poles IEC Conventional free air thermal current

Ith [A]: 25 Mounting form: P25 - Plastic enclosure with red/yellow handle Series: 7GN - round-shaped contact block Order code

7GN2592P25

Weight [g] 339.2

Qty. per package 1

Multiple qty. of packs per order 1
Package dimensions [mm] 097X097X143
Volume [cm³] 1345.487
Bar code [EAN13] 3850144004870
HS Code 85365080
68.4 £
ETIM for 7GN2592P25 Low-voltage industrial controls and switchgear (EC001105)
Feature Name
Feature Value
Type of control element (EF006976)
Short thumb-grip
Type of electrical connection of main circuit (EF006819)
Screw connection
Degree of protection (IP), front side (EF003118)
IP40
Housing material (EF001596)
Plastic
Model (EF000010)
On/Off switch
Complete device in housing (EF007317)
Yes
Suitable for intermediate mounting (EF007264)
No
Suitable for distribution board installation (EF007262)
Yes
Suitable for front mounting (EF007246)
No
Suitable for floor mounting (EF007243)
No
With retraction in 0-position (EF002428)
No
With zero (off) position (EF001416)
Yes
Number of poles (EF001391)
4
Rated permanent current I_u (EF001389)
25 A
Rated operation power at AC-3, 400 V (EF001364)
7.5 kW

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / 7GN2592P25 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.