

INDUSTRIAL COMPONENT DATA

GX3292U LOVATO ROTARY CAM SWITCH, GX SERIES, U VERSION FRONT MOUNT. ON/OFF SWITCH, FOUR-POLE - 2 WAFERS - S..

Brand: LOVATO ELECTRIC | Manufacturer Part Number: GX3292U



Manufacturer	LOVATO ELECTRIC
MPN / Reference	GX3292U
Catalog number	10000
Category	Off-load switch
Minimum order	1 Pcs
Document ID	EO-10172AA8AD
Generated	2026-08-03

Product Overview

ROTARY CAM SWITCH, GX SERIES, U VERSION FRONT MOUNT. ON/OFF SWITCH, FOUR-POLE - 2 WAFERS - SCHEME 92, 32A

4P 2POS SWITCH GX3292U FRONT MOUNTING

Rotary cam switch GX series, ON-OFF switch 4 poles 32A, for front mounting with black handle, front plate 65X65mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	LOVATO ELECTRIC > Rotary cam switches - LOVATO ELECTRIC
--------------	---

Additional Product Information

GX3292U

Rotary cam switch GX series, ON-OFF switch 4 poles 32A, for front mounting with black handle, front plate 65X65mm

Technical specifications

Type of product:ON/OFF switchesSwitching diagram:92 - ON/OFF switch 4 polesIEC Conventional free air thermal current

Ith [A]:32Mounting form:U - Front mounting with black handleSeries:GX - square-shaped contact blockOrder code

GX3292U

Weight [g] 252

Qty. per package 1

Multiple qty. of packs per order 1

Package dimensions [mm] 068X068X103

Volume [cm³] 476.272
Bar code [EAN13] 8013975104088
HS Code 85365080
61.69 £
ETIM for GX3292U Low-voltage industrial controls and switchgear (EC001105)
Feature Name
Feature Value
Type of control element (EF006976)
Short thumb-grip
Type of electrical connection of main circuit (EF006819)
Screw connection
Degree of protection (IP), front side (EF003118)
IP65
Housing material (EF001596)
Plastic
Model (EF000010)
On/Off switch
Complete device in housing (EF007317)
Yes
Suitable for intermediate mounting (EF007264)
No
Suitable for distribution board installation (EF007262)
Yes
Suitable for front mounting (EF007246)
Yes
Suitable for floor mounting (EF007243)
No
With retraction in 0-position (EF002428)
No
With zero (off) position (EF001416)
Yes
Number of poles (EF001391)
4
Rated permanent current I_u (EF001389)
32 A
Rated operation power at AC-3, 400 V (EF001364)
11 kW

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / GX3292U with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.