

INDUSTRIAL COMPONENT DATA

GX1692U11 LOVATO ROTARY CAM SWITCHE, GX SERIES, U11 VERSION FRONT MOUNT WITH HANDLE OPERATION, FOR CENTRAL 2..

Brand: LOVATO ELECTRIC | Manufacturer Part Number: GX1692U11



Manufacturer	LOVATO ELECTRIC
MPN / Reference	GX1692U11
Catalog number	10000
Category	Off-load switch
Minimum order	1 Pcs
Document ID	EO-68CDC6DCC6
Generated	2026-08-05

Product Overview

ROTARY CAM SWITCHE, GX SERIES, U11 VERSION FRONT MOUNT WITH HANDLE OPERATION, FOR CENTRAL 22MM FIXING. ON/OFF SWITCH, FOUR-POLE - 2 WAFERS - SCHEME 92, 16A

4P 2POS.SWITCH FRN/MNTG HANDLE 22MM

Rotary cam switch GX series, ON-OFF switch 4 poles 16A, for front mounting with black handle without front plate for hole Ø22mm fixing

ROTARY CAM SWITCH GX SERIES, ON-OFF SWITCH 4 POLES 16A, FOR FRONT MOUNTING WITH BLACK HANDLE WITHOUT FRONT PLATE FOR HOLE DIAM. 22MM FIXING

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	LOVATO ELECTRIC > Rotary cam switches - LOVATO ELECTRIC
--------------	---

Additional Product Information

GX1692U11

Rotary cam switch GX series, ON-OFF switch 4 poles 16A, for front mounting with black handle without front plate for hole Ø22mm fixing

Technical specifications

Type of product:ON/OFF switchesSwitching diagram:92 - ON/OFF switch 4 polesIEC Conventional free air thermal current Ith [A]:16Mounting form:U11 - Front mounting with black handle without front plate for hole diam. 22mm fixingSeries:GX - square-shaped contact blockOrder code GX1692U11

Weight [g] 123
Qty. per package 1
Multiple qty. of packs per order 1
Package dimensions [mm] 050X068X082
Volume [cm³] 278.8
Bar code [EAN13] 8013975100912
HS Code 85365080
38.63 £
ETIM for GX1692U11 Low-voltage industrial controls and switchgear (EC001105)
Feature Name
Feature Value
Type of control element (EF006976)
Short thumb-grip
Type of electrical connection of main circuit (EF006819)
Screw connection
Degree of protection (IP), front side (EF003118)
IP65
Housing material (EF001596)
Plastic
Model (EF000010)
On/Off switch
Complete device in housing (EF007317)
Yes
Suitable for intermediate mounting (EF007264)
No
Suitable for distribution board installation (EF007262)
Yes
Suitable for front mounting (EF007246)
Yes
Suitable for floor mounting (EF007243)
No
With retraction in 0-position (EF002428)
No
With zero (off) position (EF001416)
Yes
Number of poles (EF001391)
4
Rated permanent current I_u (EF001389)
16 A
Rated operation power at AC-3, 400 V (EF001364)
4.5 kW

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / GX1692U11 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.