

## INDUSTRIAL COMPONENT DATA

**BF38T2A110 LOVATO FOUR-POLE CONTACTOR, IEC OPERATING CURRENT ITH (AC1) 56A, AC COIL 50/60HZ, 110VAC, 2NO AND..**

Brand: LOVATO ELECTRIC | Manufacturer Part Number: BF38T2A110



|                 |                               |
|-----------------|-------------------------------|
| Manufacturer    | LOVATO ELECTRIC               |
| MPN / Reference | BF38T2A110                    |
| Catalog number  | 10000                         |
| Category        | Power contactor, AC switching |
| Minimum order   | 1 Pcs                         |
| Document ID     | EO-45A63FD4F8                 |
| Generated       | 2026-08-04                    |

**Product Overview**

FOUR-POLE CONTACTOR, IEC OPERATING CURRENT ITH (AC1) = 56A, AC COIL 50/60HZ, 110VAC, 2NO AND 2NC  
4P CONTACTOR 2NO+2NC 56A 110V 50/60HZ

Four-pole contactor, IEC operating current Ith (AC1) = 56A, AC coil 50/60Hz, 110VAC, 2NO and 2NC

## STRUCTURED PRODUCT DATA

**Technical Specifications**

No structured technical attributes are currently available. Submit an RFQ for technical review.

**Classification & Catalog Path**

|              |                                                                           |
|--------------|---------------------------------------------------------------------------|
| Catalog path | LOVATO ELECTRIC > Industrial Contactors and Accessories - LOVATO ELECTRIC |
|--------------|---------------------------------------------------------------------------|

**Additional Product Information**

BF38T2A110

Four-pole contactor, IEC operating current Ith (AC1) = 56A, AC coil 50/60Hz, 110VAC, 2NO and 2NC

Technical specifications

Type of product: Contactors  
Number of poles: 4  
Type of coil: AC coil 50/60Hz  
Rated coil voltage [V]: 110  
IEC operating current Ith (AC1) [A]: 56  
IEC operating current and power Ie (AC3) 400V [A/Kw]: 38A / 18.5Kw  
UL/CSA horsepower ratings 480V [HP]: 30  
Type of mounting: Screw / DIN rail 35mm  
Order code BF38T2A110

Weight [g] 510

Qty. per package 1

Multiple qty. of packs per order 1

Package dimensions [mm] 097X065X090

Volume [cm³] 567.45

Bar code [EAN13] 8013975162316  
HS Code 85365080  
325.58 £  
ETIM for BF38T2A110 Low-voltage industrial controls and switchgear (EC000066)  
Feature Name  
Feature Value  
Voltage type for actuating (EF008242)  
AC  
Type of electrical connection of main circuit (EF006819)  
Screw connection  
Rated control supply voltage AC 60 Hz (EF003979)  
110 V  
Rated control supply voltage AC 50 Hz (EF003978)  
110 V  
Modular version (EF001126)  
No  
Rated operation current I<sub>e</sub> at AC-1, 400 V (EF001393)  
56 A  
Rated operation current I<sub>e</sub> at AC-3, 400 V (EF001392)  
38 A  
Number of auxiliary contacts as normally closed contact (EF001377)  
0  
Number of auxiliary contacts as normally open contact (EF001376)  
0  
Number of normally closed contacts as main contact (EF001375)  
2  
Number of normally open contacts as main contact (EF001374)  
2

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / BF38T2A110 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.