

INDUSTRIAL COMPONENT DATA

GE0315T4 LOVATO FOUR-POLE SWITCH DISCONNECTOR, 315A

Brand: LOVATO ELECTRIC | Manufacturer Part Number: GE0315T4

Manufacturer	LOVATO ELECTRIC
MPN / Reference	GE0315T4
Catalog number	10000
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-7E32C2F72D
Generated	2026-08-04

Product Overview

FOUR-POLE SWITCH DISCONNECTOR, 315A

4P SWITCH DISCONNECTOR

Four-pole switch disconnecter, 315A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **LOVATO ELECTRIC > Switch disconnectors - LOVATO ELECTRIC**

Additional Product Information

GE0315T4

Four-pole switch disconnecter, 315A

Technical specifications

Type of product:Switch disconnectorsNumber of poles:4Type of operating voltage:ACIEC Conventional free air thermal current Ith [A]:315Type of installation:Screw on plateOrder code GE0315T4

Weight [g] 2136

Qty. per package 1

Multiple qty. of packs per order 1

Package dimensions [mm] 250X225X114

Volume [cm³] 6412.5

Bar code [EAN13] 8013975175934

HS Code 85365080

361.06 £

ETIM for GE0315T4 Low-voltage industrial controls and switchgear (EC000216)

Feature Name

Feature Value

Device construction (EF008240)

Built-in device fixed built-in technique

Type of control element (EF006976)

Door coupling rotary drive

Type of electrical connection of main circuit (EF006819)

Bolt connection

Rated operating voltage (EF001435)

400 V

Version as reversing switch (EF009408)

No

Voltage release optional (EF007491)

No

Motor drive optional (EF007386)

No

Suitable for distribution board installation (EF007262)

No

Suitable for front mounting 4-hole (EF007247)

No

Version as maintenance-/service switch (EF006986)

Yes

Version as safety switch (EF006985)

No

Version as main switch (EF006981)

Yes

Version as emergency stop installation (EF006959)

No

Motor drive integrated (EF006697)

No

Interlockable (EF006281)

No

Rated permanent current at AC-23, 400 V (EF011777)

315 A

Rated permanent current at AC-21, 400 V (EF009165)

315 A

Max. rated operation voltage Ue AC (EF007355)

690 V

Rated short-time withstand current Icw (EF007050)

12 kA

Rated opera...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / GE0315T4 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.