

INDUSTRIAL COMPONENT DATA

GX2066O48 LOVATO Voltmeter switch RS-ST-TR-0-RN-SN-TN O48 GX66 Model 20A DIN

Brand: LOVATO ELECTRIC | Manufacturer Part Number: GX2066O48



Manufacturer	LOVATO ELECTRIC
MPN / Reference	GX2066O48
Catalog number	10000
Category	Selector switch, complete
Minimum order	1 Pcs
Document ID	EO-1D1BC550FB
Generated	2026-08-03

Product Overview

Voltmeter switch RS-ST-TR-0-RN-SN-TN O48 GX66 Model 20A DIN

Conn. GX66 Voltmeter 20 A Mod. O48 DIN

Rotary cam switch GX series, voltmeter switch for phase-neutral and phase-phase voltages 20A, modular service cover for 35mm DIN rail mounting with black handle, front plate 45X54mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LOVATO ELECTRIC > Rotary cam switches - LOVATO ELECTRIC

Additional Product Information

GX2066O48

Rotary cam switch GX series, voltmeter switch for phase-neutral and phase-phase voltages 20A, modular service cover for 35mm DIN rail mounting with black handle, front plate 45X54mm

Technical specifications

Type of product: Voltmeters and ammeters
Switching diagram: 66 - Voltmeter switch for phase-neutral and phase-phase voltages
IEC Conventional free air thermal current I_{th} [A]: 20
Mounting form: O48 - Modular service cover for 35mm din rail mounting with black handle
Series: GX - square-shaped contact block
Order code GX2066O48

Weight [g] 113

Qty. per package 1

Multiple qty. of packs per order 1

Package dimensions [mm] 050X068X099

Volume [cm³] 336.6

Bar code [EAN13] 8013975105719
HS Code 85365080
ETIM for GX2066O48 Low-voltage industrial controls and switchgear (EC001029)
Feature Name
Feature Value
Type of control element (EF006976)
Short thumb-grip
Material front ring (EF005972)
Plastic
Degree of protection (IP) (EF005474)
IP65
Type of electric connection (EF003961)
Screw connection
With front ring (EF006014)
No
With light source (EF005905)
No
Spring-return (EF001407)
No
Suitable for lighting (EF001142)
No
Number of contacts as change-over contact (EF008257)
0
Number of contacts as normally open contact (EF008256)
3
Number of contacts as normally closed contact (EF008255)
0
Height opening (EF004778)
45 mm
Width opening (EF004565)
54 mm
Number of switch positions (EF000231)
7
Hole diameter (EF000079)
45 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / GX2066O48 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.