

INDUSTRIAL COMPONENT DATA

KBL2L02 LOVATO LIMIT SWITCH, K SERIES, ADJUSTABLE ROLLER LEVER, 1 BOTTOM CABLE ENTRY. DIMENSIONS TO EN 50047..

Brand: LOVATO ELECTRIC | Manufacturer Part Number: KBL2L02



Manufacturer	LOVATO ELECTRIC
MPN / Reference	KBL2L02
Catalog number	10000
Category	End switch
Minimum order	1 Pcs
Document ID	EO-C36CDF7D7A
Generated	2026-08-06

Product Overview

LIMIT SWITCH, K SERIES, ADJUSTABLE ROLLER LEVER, 1 BOTTOM CABLE ENTRY. DIMENSIONS TO EN 50047, PLASTIC BODY, CONTACTS 2NC SLOW BREAK. METAL ROD
 ADJ METAL ROD LEVER 2NC SLOW BREAK
 Limit switch, K series, adjustable roller lever, 1 bottom cable entry. Dimensions to EN 50047, plastic body, contacts 2NC slow action. Metal rod

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **LOVATO ELECTRIC > Limit, micro and foot switches - LOVATO ELECTRIC**

Additional Product Information

KBL2L02

Limit switch, K series, adjustable roller lever, 1 bottom cable entry. Dimensions to EN 50047, plastic body, contacts 2NC slow action. Metal rod

Technical specifications

Type of product: Metal and plastic limit switches
 Product characteristics: Adjustable rod lever
 Housing material: Polymer thermoplastic
 Rod characteristics: Steel
 Type of contacts: 2NC Slow action
 Cable entry: M20 on the bottom
 Order code

KBL2L02

Weight [g] 118

Qty. per package 1

Multiple qty. of packs per order 1
Package dimensions [mm] 216X041X044
Volume [cm³] 389.664
Bar code [EAN13] 8013975114940
HS Code 85365080
40.58 £
ETIM for KBL2L02 Sensors (EC000030)
Feature Name
Feature Value
Alignment of the control element (EF008793)
Other
Type of interface (EF006977)
None
Type of control element (EF006976)
Actuating rod
Degree of protection (IP) (EF005474)
IP65
Construction type housing (EF004008)
Cuboid
Explosion safety category for dust (EF003998)
None
Explosion safety category for gas (EF003997)
None
Type of electric connection (EF003961)
Cable entry metrical
Type of interface for safety communication (EF003956)
None
Coating housing (EF001601)
Other
Housing material (EF001596)
Plastic
Switching function (EF000189)
Slow-action switch
Ambient temperature during operating (EF007515)
-25 °C
Switching function latching (EF007447)
No
Output electronic (EF006987)
No
Forced opening (EF006694)
Yes
With status indication (EF001602)
No
Suitable for safety functions (EF001597)
No
Number of contacts as change-over contact (E...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / KBL2L02 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.