

INDUSTRIAL COMPONENT DATA

KML2L03 LOVATO LIMIT SWITCH, K SERIES, ADJUSTABLE ROLLER LEVER, 1 BOTTOM CABLE ENTRY. DIMENSIONS TO EN 50047..

Brand: LOVATO ELECTRIC | Manufacturer Part Number: KML2L03



Manufacturer	LOVATO ELECTRIC
MPN / Reference	KML2L03
Catalog number	10000
Category	End switch
Minimum order	1 Pcs
Document ID	EO-A5B4B80125
Generated	2026-08-06

Product Overview

LIMIT SWITCH, K SERIES, ADJUSTABLE ROLLER LEVER, 1 BOTTOM CABLE ENTRY. DIMENSIONS TO EN 50047, METAL BODY, CONTACTS 3NC SLOW BREAK. METAL ROD
ADJ METAL ROD LEVER 3NC SLOW BREAK
Limit switch, K series, adjustable roller lever, 1 bottom cable entry. Dimensions to EN 50047, metal body, contacts 3NC slow action. Metal rod

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	LOVATO ELECTRIC > Limit, micro and foot switches - LOVATO ELECTRIC
--------------	--

Additional Product Information

KML2L03

Limit switch, K series, adjustable roller lever, 1 bottom cable entry. Dimensions to EN 50047, metal body, contacts 3NC slow action. Metal rod

Technical specifications

Type of product: Metal and plastic limit switches
Product characteristics: Adjustable rod lever
Housing material: Aluminium-zinc alloy
Rod characteristics: Steel
Type of contacts: 3NC Slow action
Cable entry: M20 on the bottom
Order code KML2L03

Weight [g] 204

Qty. per package 1

Multiple qty. of packs per order 1

Package dimensions [mm] 216X041X044

Volume [cm³] 389.664

Bar code [EAN13] 8013975116968

HS Code 85365080

62.16 £

ETIM for KML2L03 Sensors (EC000030)

Feature Name

Feature Value

Alignment of the control element (EF008793)

Other

Type of interface (EF006977)

None

Type of control element (EF006976)

Actuating rod

Degree of protection (IP) (EF005474)

IP65

Construction type housing (EF004008)

Cuboid

Explosion safety category for dust (EF003998)

None

Explosion safety category for gas (EF003997)

None

Type of electric connection (EF003961)

Cable entry metrical

Type of interface for safety communication (EF003956)

None

Coating housing (EF001601)

Powder coated

Housing material (EF001596)

Metal

Switching function (EF000189)

Slow-action switch

Ambient temperature during operating (EF007515)

-25 °C

Switching function latching (EF007447)

No

Output electronic (EF006987)

No

Forced opening (EF006694)

Yes

With status indication (EF001602)

No

Suitable for safety functions (EF001597)

No

Number of contacts as change-over contact...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / KML2L03 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.