

INDUSTRIAL COMPONENT DATA

ADXNB00624 LOVATO SOFT STARTER 6A AUX 24VAC/DC BASIC

Brand: LOVATO ELECTRIC | Manufacturer Part Number: ADXNB00624



Manufacturer	LOVATO ELECTRIC
MPN / Reference	ADXNB00624
Catalog number	00624
Category	Soft starter
Minimum order	1 Pcs
Document ID	EO-B7628B1751
Generated	2026-07-29

Product Overview

SOFT STARTER 6A AUX 24VAC/DC BASIC

Soft starter, ADXNB... type, basic version, with integrated by-pass relay. Auxiliary supply 24VAC/DC. Rated operational voltage 208...600VAC, 6A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LOVATO ELECTRIC > Soft Starters / Starters Static - LOVATO ELECTRIC

Additional Product Information

ADXNB00624

Soft starter, ADXNB... type, basic version, with integrated by-pass relay. Auxiliary supply 24VAC/DC. Rated operational voltage 208...600VAC, 6A

Technical specifications

Type of product:Ultra compact, two phase controlVersion:BasicNumber of controlled phases:2Rated operational voltage:208...600VACRated supply voltage:24VAC/DCRated starter current I_e [A]:6Rated motor power 230VAC [kW]:1.1Rated motor power 400VAC [kW]:2.2Rated motor power 500VAC [kW]:3Functions:Basic parameters onlyOrder code ADXNB00624

Weight [g] 540

Qty. per package 1

Multiple qty. of packs per order 1

Package dimensions [mm] 185X176X084

Volume [cm³] 2800

Bar code [EAN13] 8013975298978

HS Code 85044090

134.68 £

ETIM for ADXNB00624 Low-voltage industrial controls and switchgear (EC000640)

Feature Name

Feature Value

Voltage type for actuating (EF008242)

AC/DC

Degree of protection (IP) (EF005474)

IP20

Rated control supply voltage DC (EF003980)

24 V

Rated control supply voltage AC 60 Hz (EF003979)

24 V

Rated control supply voltage AC 50 Hz (EF003978)

24 V

Rated operating voltage Ue (EF002418)

208 V

Torque control (EF009215)

No

Internal bypass (EF009214)

No

Integrated motor overload protection (EF007297)

No

With display (EF000458)

No

Rated surrounding temperature without derating (EF007074)

60 °C

Rated power three-phase motor, inline, at 400 V (EF007054)

2.2 kW

Rated power three-phase motor, inline, at 230 V (EF007053)

1.1 kW

Rated operation current Ie at 40 °C Tu (EF007039)

6 A

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / ADXNB00624 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.