

INDUSTRIAL COMPONENT DATA

ADXNB012 LOVATO SOFT STARTER 12A AUX 100-240VAC
BASIC

Brand: LOVATO ELECTRIC | Manufacturer Part Number: ADXNB012



Manufacturer	LOVATO ELECTRIC
MPN / Reference	ADXNB012
Catalog number	10000
Category	Soft starter
Minimum order	1 Pcs
Document ID	EO-33C3D0D496
Generated	2026-07-28

Product Overview

SOFT STARTER 12A AUX 100-240VAC BASIC

Soft starter, ADXNB... type, basic version, with integrated by-pass relay. Auxiliary supply 100...240VAC. Rated operational voltage 208...600VAC, 12A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LOVATO ELECTRIC > Soft Starters / Starters Static - LOVATO ELECTRIC

Additional Product Information

ADXNB012

Soft starter, ADXNB... type, basic version, with integrated by-pass relay. Auxiliary supply 100...240VAC. Rated operational voltage 208...600VAC, 12A

Technical specifications

Type of product:Ultra compact, two phase controlVersion:BasicNumber of controlled phases:2Rated operational voltage:208...600VACRated supply voltage:100...240VACRated starter current I_e [A]:12Rated motor power 230VAC [kW]:3Rated motor power 400VAC [kW]:5.5Rated motor power 500VAC [KW]:5.5Functions:Basic parameters onlyOrder code ADXNB012

Weight [g] 540

Qty. per package 1

Multiple qty. of packs per order 1

Package dimensions [mm] 185X176X084

Volume [cm³] 2800

Bar code [EAN13] 8013975298985

HS Code 85044090

150.84 £

ETIM for ADXNB012 Low-voltage industrial controls and switchgear (EC000640)

Feature Name

Feature Value

Voltage type for actuating (EF008242)

AC

Degree of protection (IP) (EF005474)

IP20

Rated control supply voltage AC 60 Hz (EF003979)

100 V

Rated control supply voltage AC 50 Hz (EF003978)

100 V

Rated operating voltage Ue (EF002418)

208 V

Torque control (EF009215)

No

Internal bypass (EF009214)

No

Integrated motor overload protection (EF007297)

No

With display (EF000458)

No

Rated surrounding temperature without derating (EF007074)

60 °C

Rated power three-phase motor, inline, at 400 V (EF007054)

5.5 kW

Rated power three-phase motor, inline, at 230 V (EF007053)

3 kW

Rated operation current Ie at 40 °C Tu (EF007039)

12 A

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / ADXNB012 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.