

INDUSTRIAL COMPONENT DATA

ADXNB03024 LOVATO SOFT STARTER 30A AUX 24VAC/DC
BASIC

Brand: LOVATO ELECTRIC | Manufacturer Part Number: ADXNB03024



Manufacturer	LOVATO ELECTRIC
MPN / Reference	ADXNB03024
Catalog number	03024
Category	Soft starter
Minimum order	1 Pcs
Document ID	EO-796977DCAA
Generated	2026-07-31

Product Overview

SOFT STARTER 30A AUX 24VAC/DC BASIC

Soft starter, ADXNB... type, basic version, with integrated by-pass relay. Auxiliary supply 24VAC/DC. Rated operational voltage 208...600VAC, 30A

-

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LOVATO ELECTRIC > Soft Starters / Starters Static - LOVATO ELECTRIC

Additional Product Information

ADXNB03024

Soft starter, ADXNB... type, basic version, with integrated by-pass relay. Auxiliary supply 24VAC/DC. Rated operational voltage 208...600VAC, 30A

Technical specifications

Type of product: Ultra compact, two phase control
Version: Basic
Number of controlled phases: 2
Rated operational voltage: 208...600VAC
Rated supply voltage: 24VAC/DC
Rated starter current I_e [A]: 30
Rated motor power 230VAC [kW]: 7.5
Rated motor power 400VAC [kW]: 15
Rated motor power 500VAC [kW]: 18.5
Functions: Basic parameters only
Order code ADXNB03024

Weight [g] 720

Qty. per package 1

Multiple qty. of packs per order 1

Package dimensions [mm] 185X176X084

Volume [cm³] 2800
Bar code [EAN13] 8013975299050
HS Code 85044090
231.65 £
ETIM for ADXNB03024 Low-voltage industrial controls and switchgear (EC000640)
Feature Name
Feature Value
Voltage type for actuating (EF008242)
AC/DC
Degree of protection (IP) (EF005474)
IP20
Rated control supply voltage DC (EF003980)
24 V
Rated control supply voltage AC 60 Hz (EF003979)
24 V
Rated control supply voltage AC 50 Hz (EF003978)
24 V
Rated operating voltage U_e (EF002418)
208 V
Torque control (EF009215)
No
Internal bypass (EF009214)
No
Integrated motor overload protection (EF007297)
No
With display (EF000458)
No
Rated surrounding temperature without derating (EF007074)
60 °C
Rated power three-phase motor, inline, at 400 V (EF007054)
15 kW
Rated power three-phase motor, inline, at 230 V (EF007053)
7.5 kW
Rated operation current I_e at 40 °C T_u (EF007039)
30 A

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / ADXNB03024 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.