

INDUSTRIAL COMPONENT DATA

ADXNB04524 LOVATO SOFT STARTER 45A AUX 24VAC/DC
BASIC

Brand: LOVATO ELECTRIC | Manufacturer Part Number: ADXNB04524



Manufacturer	LOVATO ELECTRIC
MPN / Reference	ADXNB04524
Catalog number	04524
Category	Soft starter
Minimum order	1 Pcs
Document ID	EO-B6DDAF9BC1
Generated	2026-07-28

Product Overview

SOFT STARTER 45A AUX 24VAC/DC BASIC

Soft starter, ADXNB... type, basic version, with integrated by-pass relay, built-in fan. Auxiliary supply 24VAC/DC. Rated operational voltage 208...600VAC, 45A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LOVATO ELECTRIC > Soft Starters / Starters Static - LOVATO ELECTRIC

Additional Product Information

ADXNB04524

Soft starter, ADXNB... type, basic version, with integrated by-pass relay, built-in fan. Auxiliary supply 24VAC/DC. Rated operational voltage 208...600VAC, 45A

Technical specifications

Type of product:Ultra compact, two phase controlVersion:BasicNumber of controlled phases:2Rated operational voltage:208...600VACRated supply voltage:24VAC/DCRated starter current I_e [A]:45Rated motor power 230VAC [kW]:11Rated motor power 400VAC [kW]:22Rated motor power 500VAC [KW]:30Functions:Basic parameters onlyOrder code ADXNB04524

Weight [g] 750

Qty. per package 1

Multiple qty. of packs per order 1

Package dimensions [mm] 185X176X084

Volume [cm³] 2800

Bar code [EAN13] 8013975299098

HS Code 85044090

371.72 £

ETIM for ADXNB04524 Low-voltage industrial controls and switchgear (EC000640)

Feature Name

Feature Value

Voltage type for actuating (EF008242)

AC/DC

Degree of protection (IP) (EF005474)

IP20

Rated control supply voltage DC (EF003980)

24 V

Rated control supply voltage AC 60 Hz (EF003979)

24 V

Rated control supply voltage AC 50 Hz (EF003978)

24 V

Rated operating voltage Ue (EF002418)

208 V

Torque control (EF009215)

No

Internal bypass (EF009214)

No

Integrated motor overload protection (EF007297)

No

With display (EF000458)

No

Rated surrounding temperature without derating (EF007074)

60 °C

Rated power three-phase motor, inline, at 400 V (EF007054)

22 kW

Rated power three-phase motor, inline, at 230 V (EF007053)

11 kW

Rated operation current Ie at 40 °C Tu (EF007039)

45 A

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / ADXNB04524 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.