

INDUSTRIAL COMPONENT DATA

ADXNF00624 LOVATO SOFT STARTER 6A AUX 24VAC/DC NFC

Brand: LOVATO ELECTRIC | Manufacturer Part Number: ADXNF00624



Manufacturer	LOVATO ELECTRIC
MPN / Reference	ADXNF00624
Catalog number	00624
Category	Soft starter
Minimum order	1 Pcs
Document ID	EO-16899F194D
Generated	2026-08-03

Product Overview

SOFT STARTER 6A AUX 24VAC/DC NFC

Static starter, ADXNF series..., NFC version, with built-in bypass relay. Auxiliary power supply 24VAC/DC. Operating voltage 208...600VAC, 6A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **LOVATO ELECTRIC > Soft Starters / Starters Static - LOVATO ELECTRIC**

Additional Product Information

ADXNF00624

Static starter, ADXNF series..., NFC version, with built-in bypass relay. Auxiliary power supply 24VAC/DC. Operating voltage 208...600VAC, 6A

Technical Specifications

Product Type:Ultra-compact, two-phase controlTypology:NFCNumber of phases controlled:2Rated Operating Voltage:208... 600VACNominal Supply Voltage:24VAC/DCRated starting current I_e [A]:6Motor power rating 230VAC [KW]:1.1Motor power rating 400VAC [KW]:2.2Motor power rating 500VAC [KW]:3Functions:NFC, passwordOrder Code ADXNF00624

Weight [g] 540

Packaging units 1

Multi-pack order quantity 1

Packaging dimensions [mm] 185X176X084

Volume [cm³] 2800

Barcode [EAN13] 8013975299111
HS Code 85044090
ETIM for ADXNF00624 Low-voltage industrial controls and switchgear (EC000640)
Feature Name
Feature Value
Voltage type for actuating (EF008242)
AC/DC
Degree of protection (IP) (EF005474)
IP20
Rated control supply voltage DC (EF003980)
24 V
Rated control supply voltage AC 60 Hz (EF003979)
24 V
Rated control supply voltage AC 50 Hz (EF003978)
24 V
Rated operating voltage Ue (EF002418)
208 V
Torque control (EF009215)
No
Internal bypass (EF009214)
No
Integrated motor overload protection (EF007297)
No
With display (EF000458)
No
Rated surrounding temperature without derating (EF007074)
60 °C
Rated power three-phase motor, inline, at 400 V (EF007054)
2.2 kW
Rated power three-phase motor, inline, at 230 V (EF007053)
1.1 kW
Rated operation current Ie at 40 °C Tu (EF007039)
6 A

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / ADXNF00624 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.