

INDUSTRIAL COMPONENT DATA

ADXNF045 LOVATO SOFT STARTER 45A AUX 100-240VAC NFC

Brand: LOVATO ELECTRIC | Manufacturer Part Number: ADXNF045



Manufacturer	LOVATO ELECTRIC
MPN / Reference	ADXNF045
Catalog number	10000
Category	Soft starter
Minimum order	1 Pcs
Document ID	EO-33AFFEDAE2
Generated	2026-08-01

Product Overview

SOFT STARTER 45A AUX 100-240VAC NFC

Soft starter, ADXNF... type, NFC version, with integrated by-pass relay, built-in fan. Auxiliary supply 100...240VAC. Rated operational voltage 208...600VAC, 45A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LOVATO ELECTRIC > Soft Starters / Starters Static - LOVATO ELECTRIC

Additional Product Information

ADXNF045

Soft starter, ADXNF... type, NFC version, with integrated by-pass relay, built-in fan. Auxiliary supply 100...240VAC. Rated operational voltage 208...600VAC, 45A

Technical specifications

Type of product:Ultra compact, two phase controlVersion:NFCNumber of controlled phases:2Rated operational voltage:208...600VACRated supply voltage:100...240VACRated starter current I_e [A]:45Rated motor power 230VAC [kW]:11Rated motor power 400VAC [kW]:22Rated motor power 500VAC [KW]:30Functions:NFC, passwordOrder code ADXNF045

Weight [g] 760

Qty. per package 1

Multiple qty. of packs per order 1

Package dimensions [mm] 185X176X084

Volume [cm³] 2800
Bar code [EAN13] 8013975299227
HS Code 85044090
371.72 £
ETIM for ADXNF045 Low-voltage industrial controls and switchgear (EC000640)
Feature Name
Feature Value
Voltage type for actuating (EF008242)
AC
Degree of protection (IP) (EF005474)
IP20
Rated control supply voltage AC 60 Hz (EF003979)
100 V
Rated control supply voltage AC 50 Hz (EF003978)
100 V
Rated operating voltage U_e (EF002418)
208 V
Torque control (EF009215)
No
Internal bypass (EF009214)
No
Integrated motor overload protection (EF007297)
No
With display (EF000458)
No
Rated surrounding temperature without derating (EF007074)
60 °C
Rated power three-phase motor, inline, at 400 V (EF007054)
22 kW
Rated power three-phase motor, inline, at 230 V (EF007053)
11 kW
Rated operation current I_e at 40 °C T_u (EF007039)
45 A

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / ADXNF045 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.