

INDUSTRIAL COMPONENT DATA

ADXNP018 LOVATO SOFT STARTER 18A AUX 100-240VAC
ADVANCED

Brand: LOVATO ELECTRIC | Manufacturer Part Number: ADXNP018



Manufacturer	LOVATO ELECTRIC
MPN / Reference	ADXNP018
Catalog number	10000
Category	Soft starter
Minimum order	1 Pcs
Document ID	EO-292E6284DE
Generated	2026-08-01

Product Overview

SOFT STARTER 18A AUX 100-240VAC ADVANCED

Soft starter, ADXNP... type, advanced version, with integrated bypass relay. Auxiliary supply 100...240VAC. Rated operational voltage 208...600VAC, 18A

-

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LOVATO ELECTRIC > Soft Starters / Starters Static - LOVATO ELECTRIC

Additional Product Information

ADXNP018

Soft starter, ADXNP... type, advanced version, with integrated bypass relay. Auxiliary supply 100...240VAC. Rated operational voltage 208...600VAC, 18A

Technical specifications

Type of product: Ultra compact, two phase control
Version: Advanced
Number of controlled phases: 2
Rated operational voltage: 208...600VAC
Rated supply voltage: 100...240VAC
Rated starter current I_e [A]: 18
Rated motor power 230VAC [kW]: 4
Rated motor power 400VAC [kW]: 7.5
Rated motor power 500VAC [kW]: 11
Functions: NFC, motor current thermal protection, starting with current limit, optical port, optional RS485
Order code ADXNP018

Weight [g] 560

Qty. per package 1

Multiple qty. of packs per order 1

Package dimensions [mm] 185X176X084

Volume [cm³] 2800
Bar code [EAN13] 8013975299289
HS Code 85044090
188.55 £
ETIM for ADXNP018 Low-voltage industrial controls and switchgear (EC000640)
Feature Name
Feature Value
Voltage type for actuating (EF008242)
AC
Degree of protection (IP) (EF005474)
IP20
Rated control supply voltage AC 60 Hz (EF003979)
100 V
Rated control supply voltage AC 50 Hz (EF003978)
100 V
Rated operating voltage U_e (EF002418)
208 V
Torque control (EF009215)
No
Internal bypass (EF009214)
No
Integrated motor overload protection (EF007297)
No
With display (EF000458)
No
Rated surrounding temperature without derating (EF007074)
60 °C
Rated power three-phase motor, inline, at 400 V (EF007054)
7.5 kW
Rated power three-phase motor, inline, at 230 V (EF007053)
4 kW
Rated operation current I_e at 40 °C T_u (EF007039)...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / ADXNP018 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.