

INDUSTRIAL COMPONENT DATA

ADXNP02524 LOVATO SOFT STARTER 25A AUX 24VAC/DC
ADVANCED

Brand: LOVATO ELECTRIC | Manufacturer Part Number: ADXNP02524



Manufacturer	LOVATO ELECTRIC
MPN / Reference	ADXNP02524
Catalog number	02524
Category	Soft starter
Minimum order	1 Pcs
Document ID	EO-4A03C61C24
Generated	2026-08-03

Product Overview

SOFT STARTER 25A AUX 24VAC/DC ADVANCED

Soft starter, ADXNP... type, advanced version, with integrated by-pass relay. Auxiliary supply 24VAC/DC. Rated operational voltage 208...600VAC, 25A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LOVATO ELECTRIC > Soft Starters / Starters Static - LOVATO ELECTRIC

Additional Product Information

ADXNP02524

Soft starter, ADXNP... type, advanced version, with integrated by-pass relay. Auxiliary supply 24VAC/DC. Rated operational voltage 208...600VAC, 25A

Technical specifications

Type of product:Ultra compact, two phase controlVersion:AdvancedNumber of controlled phases:2Rated operational voltage:208...600VACRated supply voltage:24VAC/DCRated starter current I_e [A]:25Rated motor power 230VAC [kW]:5.5Rated motor power 400VAC [kW]:11Rated motor power 500VAC [kW]:15Functions:NFC, motor current thermal protection, starting with current limit, optical port, optional RS485Order code ADXNP02524

Weight [g] 750

Qty. per package 1

Multiple qty. of packs per order 1

Package dimensions [mm] 185X176X084

Volume [cm³] 2800

Bar code [EAN13] 8013975299319
HS Code 85044090
263.97 £
ETIM for ADXNP02524 Low-voltage industrial controls and switchgear (EC000640)
Feature Name
Feature Value
Voltage type for actuating (EF008242)
AC/DC
Degree of protection (IP) (EF005474)
IP20
Rated control supply voltage DC (EF003980)
24 V
Rated control supply voltage AC 60 Hz (EF003979)
24 V
Rated control supply voltage AC 50 Hz (EF003978)
24 V
Rated operating voltage Ue (EF002418)
208 V
Torque control (EF009215)
No
Internal bypass (EF009214)
No
Integrated motor overload protection (EF007297)
No
With display (EF000458)
No
Rated surrounding temperature without derating (EF007074)
60 °C
Rated power three-phase motor, inline, at 400 V (EF007054)
11 kW
Rated power three-phase motor, inline, at 230 V (EF007053)
5.5....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / ADXNP02524 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.