

INDUSTRIAL COMPONENT DATA

ADXT0230 LOVATO SOFT STARTER 230A 380-690V, AUX 110/240V

Brand: LOVATO ELECTRIC | Manufacturer Part Number: ADXT0230



Manufacturer	LOVATO ELECTRIC
MPN / Reference	ADXT0230
Catalog number	ADXT0230
Category	Soft starter
Minimum order	1 Pcs
Document ID	EO-2B5257C13A
Generated	2026-08-05

Product Overview

SOFT STARTER 230A 380-690V, AUX 110/240V

Soft starter, ADXT... series, for standard and heavy-duty applications, with built-in bypass relay. Auxiliary supply voltage 110...120VAC and 220...240VAC. Rated operational voltage 380...690VAC, 230A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LOVATO ELECTRIC > Soft Starters / Starters Static - LOVATO ELECTRIC

Additional Product Information

ADXT0230

Soft starter, ADXT... series, for standard and heavy-duty applications, with built-in bypass relay. Auxiliary supply voltage 110...120VAC and 220...240VAC. Rated operational voltage 380...690VAC, 230A

Technical specifications

Type of product:Advanced, three phase controlNumber of controlled phases:3Rated operational voltage:380...690VACRated supply voltage:110...120VAC / 220...240VACRated starter current I_e [A]:230Rated motor power 400VAC [kW]:160Rated motor power 500VAC [kW]:250Order code ADXT0230

Weight [g] 14700

Qty. per package 1

Multiple qty. of packs per order 1

Package dimensions [mm] 610X330X300

Volume [cm³] 60390

Bar code [EAN13] 8013975322598

HS Code 85371098
ETIM for ADXT0230 Low-voltage industrial controls and switchgear (EC000640)
Feature Name
Feature Value
Rated control supply voltage AC 60 Hz (EF003979)
110 V
Rated control supply voltage AC 50 Hz (EF003978)
110 V
Rated operating voltage Ue (EF002418)
380 V
Rated surrounding temperature without derating (EF007074)
40 °C
Rated power three-phase motor, inside delta, at 400 V (EF007056)
160 kW
Rated power three-phase motor, inline, at 400 V (EF007054)
132 kW
Rated operation current Ie at 40 °C Tu (EF007039)
230 A
Torque control (EF009215)
No
Internal bypass (EF009214)
Yes
Integrated motor overload protection (EF007297)
Yes
With display (EF000458)
Yes
Voltage type for actuating (EF008242)
AC
Release class (EF006668)
CLASS 10
Degree of protection (IP) (EF005474)
IP00
Function (EF000030)
Single direction

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / ADXT0230 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.