

INDUSTRIAL COMPONENT DATA

ADXT023024 LOVATO SOFT STARTER 230A 380-690V, AUX 24VAC/DC

Brand: LOVATO ELECTRIC | Manufacturer Part Number: ADXT023024



Manufacturer	LOVATO ELECTRIC
MPN / Reference	ADXT023024
Catalog number	ADXT023024
Category	Soft starter
Minimum order	1 Pcs
Document ID	EO-D7467E0F08
Generated	2026-08-04

Product Overview

SOFT STARTER 230A 380-690V, AUX 24VAC/DC

Soft starter, ADXT... series, for standard and heavy-duty applications, with built-in bypass relay. Auxiliary supply voltage 24VAC/DC. Rated operational voltage 380...690VAC, 230A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LOVATO ELECTRIC > Soft Starters / Starters Static - LOVATO ELECTRIC

Additional Product Information

ADXT023024

Soft starter, ADXT... series, for standard and heavy-duty applications, with built-in bypass relay. Auxiliary supply voltage 24VAC/DC. Rated operational voltage 380...690VAC, 230A

Technical specifications

Type of product:Advanced, three phase controlNumber of controlled phases:3Rated operational voltage:380...690VACRated supply voltage:24VAC/DCRated starter current I_e [A]:230Rated motor power 400VAC [kW]:160Rated motor power 500VAC [KW]:250Order code ADXT023024

Weight [g] 14700

Qty. per package 1

Multiple qty. of packs per order 1

Package dimensions [mm] 610X330X300

Volume [cm³] 60390

Bar code [EAN13] 8013975322604

HS Code 85371098

ETIM for ADXT023024 Low-voltage industrial controls and switchgear (EC000640)

Feature Name

Feature Value

Rated control supply voltage DC (EF003980)

24 V

Rated control supply voltage AC 60 Hz (EF003979)

24 V

Rated control supply voltage AC 50 Hz (EF003978)

24 V

Rated operating voltage Ue (EF002418)

380 V

Rated surrounding temperature without derating (EF007074)

40 °C

Rated power three-phase motor, inside delta, at 400 V (EF007056)

160 kW

Rated power three-phase motor, inline, at 400 V (EF007054)

132 kW

Rated operation current Ie at 40 °C Tu (EF007039)

230 A

Torque control (EF009215)

No

Internal bypass (EF009214)

Yes

Integrated motor overload protection (EF007297)

Yes

With display (EF000458)

Yes

Voltage type for actuating (EF008242)

AC/DC

Release class (EF006668)

CLASS 10

Degree of protection (IP) (EF005474)

IP00

Function (EF000030)

Single di...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / ADXT023024 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.