

## INDUSTRIAL COMPONENT DATA

**BF12T4A22060 LOVATO FOUR-POLE CONTACTOR, IEC  
OPERATING CURRENT ITH (AC1) 28A, AC COIL 60HZ,  
220VAC**

Brand: LOVATO ELECTRIC | Manufacturer Part Number: BF12T4A22060



|                 |                               |
|-----------------|-------------------------------|
| Manufacturer    | LOVATO ELECTRIC               |
| MPN / Reference | BF12T4A22060                  |
| Catalog number  | 22060                         |
| Category        | Power contactor, AC switching |
| Minimum order   | 1 Pcs                         |
| Document ID     | EO-C2E942E043                 |
| Generated       | 2026-07-29                    |

**Product Overview**

FOUR-POLE CONTACTOR, IEC OPERATING CURRENT ITH (AC1) = 28A, AC COIL 60HZ, 220VAC

4P CONTACTOR NO 28A AC1 220/60

Four-pole contactor, IEC operating current Ith (AC1) = 28A, AC coil 60Hz, 220VAC

## STRUCTURED PRODUCT DATA

**Technical Specifications**

No structured technical attributes are currently available. Submit an RFQ for technical review.

**Classification & Catalog Path**

Catalog path LOVATO ELECTRIC &gt; Industrial Contactors and Accessories - LOVATO ELECTRIC

**Additional Product Information**

BF12T4A22060

Four-pole contactor, IEC operating current Ith (AC1) = 28A, AC coil 60Hz, 220VAC

Technical specifications

Type of product: Contactors Number of poles: 4 Type of coil: AC coil 60Hz Rated coil voltage [V]: 220 IEC operating current Ith (AC1) [A]: 28 IEC operating current and power Ie (AC3) 400V [A/Kw]: 12A / 5.7Kw UL/CSA horsepower ratings 480V [HP]: 7.5 Type of mounting: Screw / DIN rail 35mm Order code BF12T4A22060

Weight [g] 350

Qty. per package 1

Multiple qty. of packs per order 1

Package dimensions [mm] 090X047X086

Volume [cm³] 363.78

Bar code [EAN13] 8013975161531

HS Code 85365080

70.72 £

ETIM for BF12T4A22060 Low-voltage industrial controls and switchgear (EC000066)

Feature Name

Feature Value

Voltage type for actuating (EF008242)

AC

Type of electrical connection of main circuit (EF006819)

Screw connection

Rated control supply voltage AC 60 Hz (EF003979)

220 V

Modular version (EF001126)

No

Rated operation current I<sub>e</sub> at AC-4, 400 V (EF008495)

7.9 A

Rated operation current I<sub>e</sub> at AC-1, 400 V (EF001393)

28 A

Rated operation current I<sub>e</sub> at AC-3, 400 V (EF001392)

12 A

Number of auxiliary contacts as normally closed contact (EF001377)

0

Number of auxiliary contacts as normally open contact (EF001376)

0

Number of normally closed contacts as main contact (EF001375)

0

Number of normally open contacts as main contact (EF001374)

4

Rated operation power at AC-3, 400 V (EF001364)

5.7 kW

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / BF12T4A22060 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.