

INDUSTRIAL COMPONENT DATA

BF2501A57560 LOVATO THREE-POLE CONTACTOR, IEC OPERATING CURRENT IE (AC3) 25A, AC COIL 60HZ, 575VAC, 1NC AUXI..

Brand: LOVATO ELECTRIC | Manufacturer Part Number: BF2501A57560



Manufacturer	LOVATO ELECTRIC
MPN / Reference	BF2501A57560
Catalog number	57560
Category	Power contactor, AC switching
Minimum order	1 Pcs
Document ID	EO-BA574C1FA0
Generated	2026-08-02

Product Overview

THREE-POLE CONTACTOR, IEC OPERATING CURRENT IE (AC3) = 25A, AC COIL 60HZ, 575VAC, 1NC AUXILIARY CONTACT

3P CONTACTOR +1NC 25A AC3

Three-pole contactor, IEC operating current Ie (AC3) = 25A, AC coil 60Hz, 575VAC, 1NC auxiliary contact

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LOVATO ELECTRIC > Industrial Contactors and Accessories - LOVATO ELECTRIC

Additional Product Information

BF2501A57560

Three-pole contactor, IEC operating current Ie (AC3) = 25A, AC coil 60Hz, 575VAC, 1NC auxiliary contact

Technical specifications

Type of product:ContactorsNumber of poles:3Type of coil:AC coil 60HzRated coil voltage [V]:575IEC operating current Ith (AC1) [A]:32IEC operating current and power Ie (AC3) 400V [A/Kw]:25A / 12.5KwUL/CSA horsepower ratings 480V [HP]:15Type of built-in auxiliary contacts:1NCType of mounting:Screw / DIN rail 35mmOrder code BF2501A57560

Weight [g] 360

Qty. per package 1

Multiple qty. of packs per order 1

Package dimensions [mm] 090X047X086

Volume [cm³] 363.78
Bar code [EAN13] 8013975160961
HS Code 85365080
100.36 £
ETIM for BF2501A57560 Low-voltage industrial controls and switchgear (EC000066)
Feature Name
Feature Value
Voltage type for actuating (EF008242)
AC
Type of electrical connection of main circuit (EF006819)
Screw connection
Rated control supply voltage AC 60 Hz (EF003979)
575 V
Modular version (EF001126)
No
Rated operation current I_e at AC-4, 400 V (EF008495)
10 A
Rated operation current I_e at AC-1, 400 V (EF001393)
32 A
Rated operation current I_e at AC-3, 400 V (EF001392)
25 A
Number of auxiliary contacts as normally closed contact (EF001377)
1
Number of auxiliary contacts as normally open contact (EF001376)
0
Number of normally closed contacts as main contact (EF001375)
0
Number of normally open contacts as main contact (EF001374)
3
Rated operation power at AC-3, 400 V (EF001364)
12.5 kW

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / BF2501A57560 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.