

## INDUSTRIAL COMPONENT DATA

**BF4000E024 LOVATO THREE-POLE CONTACTOR, IEC OPERATING CURRENT IE (AC3) 40A, AC/DC COIL, 20...48VAC/DC**

Brand: LOVATO ELECTRIC | Manufacturer Part Number: BF4000E024



|                 |                               |
|-----------------|-------------------------------|
| Manufacturer    | LOVATO ELECTRIC               |
| MPN / Reference | BF4000E024                    |
| Catalog number  | 10000                         |
| Category        | Power contactor, AC switching |
| Minimum order   | 1 Pcs                         |
| Document ID     | EO-A1F68FE7AD                 |
| Generated       | 2026-08-04                    |

**Product Overview**

THREE-POLE CONTACTOR, IEC OPERATING CURRENT IE (AC3) = 40A, AC/DC COIL, 20...48VAC/DC

3P CONTACTOR 40A AC3 20-48VAC/DC

Three-pole contactor, IEC operating current Ie (AC3) = 40A, AC/DC coil, 20...48VAC/DC

## STRUCTURED PRODUCT DATA

**Technical Specifications**

No structured technical attributes are currently available. Submit an RFQ for technical review.

**Classification & Catalog Path**

Catalog path LOVATO ELECTRIC &gt; Industrial Contactors and Accessories - LOVATO ELECTRIC

**Additional Product Information**

BF4000E024

Three-pole contactor, IEC operating current Ie (AC3) = 40A, AC/DC coil, 20...48VAC/DC

Technical specifications

Type of product:ContactorsNumber of poles:3Type of coil:AC/DC coilRated coil voltage [V]:20...48IEC operating current Ith (AC1) [A]:70IEC operating current and power Ie (AC3) 400V [A/Kw]:40A / 18.5KwUL/CSA horsepower ratings 480V [HP]:30Type of mounting:Screw / DIN rail 35mmOrder code BF4000E024

Weight [g] 1060

Qty. per package 1

Multiple qty. of packs per order 1

Package dimensions [mm] 141X063X120

Volume [cm³] 1066

Bar code [EAN13] 8013975223932

HS Code 85365080

251.74 £

ETIM for BF4000E024 Low-voltage industrial controls and switchgear (EC000066)

Feature Name

Feature Value

Rated control supply voltage DC (EF003980)

20 V

Rated control supply voltage AC 60 Hz (EF003979)

20 V

Rated control supply voltage AC 50 Hz (EF003978)

20 V

Rated operation current I<sub>e</sub> at AC-4, 400 V (EF008495)

24 A

Rated operation current I<sub>e</sub> at AC-1, 400 V (EF001393)

70 A

Rated operation current I<sub>e</sub> at AC-3, 400 V (EF001392)

40 A

Number of auxiliary contacts as normally closed contact (EF001377)

0

Number of auxiliary contacts as normally open contact (EF001376)

0

Number of normally closed contacts as main contact (EF001375)

0

Number of normally open contacts as main contact (EF001374)

3

Rated operation power at AC-3, 400 V (EF001364)

18.5 kW

Modular version (EF001126)

No

Voltage type for actuating (EF008242)

AC/DC

Type of electrical connection of main circuit (EF006819)

Frame clamp

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / BF4000E024 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.