

INDUSTRIAL COMPONENT DATA

**BF40T4A23060 LOVATO FOUR-POLE CONTACTOR, IEC
OPERATING CURRENT ITH (AC1) 70A, AC COIL 60HZ,
230VAC**

Brand: LOVATO ELECTRIC | Manufacturer Part Number: BF40T4A23060



Manufacturer	LOVATO ELECTRIC
MPN / Reference	BF40T4A23060
Catalog number	23060
Category	Power contactor, AC switching
Minimum order	1 Pcs
Document ID	EO-A64175CE36
Generated	2026-07-29

Product Overview

FOUR-POLE CONTACTOR, IEC OPERATING CURRENT ITH (AC1) = 70A, AC COIL 60HZ, 230VAC

4P CONTACTOR 70A AC1 230VAC 60HZ

Four-pole contactor, IEC operating current Ith (AC1) = 70A, AC coil 60Hz, 230VAC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LOVATO ELECTRIC > Industrial Contactors and Accessories - LOVATO ELECTRIC

Additional Product Information

BF40T4A23060

Four-pole contactor, IEC operating current Ith (AC1) = 70A, AC coil 60Hz, 230VAC

Technical specifications

Type of product: Contactors Number of poles: 4 Type of coil: AC coil 60Hz Rated coil voltage [V]: 230 IEC operating current Ith (AC1) [A]: 70 IEC operating current and power Ie (AC3) 400V [A/Kw]: 40A /18.5Kw UL/CSA horsepower ratings 480V [HP]: 30 Type of mounting: Screw / DIN rail 35mm Order code BF40T4A23060

Weight [g] 1240

Qty. per package 1

Multiple qty. of packs per order 1

Package dimensions [mm] 141X080X120

Volume [cm³] 1354

Bar code [EAN13] 8013975222935

HS Code 85365080

179.56 £

ETIM for BF40T4A23060 Low-voltage industrial controls and switchgear (EC000066)

Feature Name

Feature Value

Voltage type for actuating (EF008242)

AC

Type of electrical connection of main circuit (EF006819)

Frame clamp

Rated control supply voltage AC 60 Hz (EF003979)

230 V

Modular version (EF001126)

No

Rated operation current I_e at AC-4, 400 V (EF008495)

24 A

Rated operation current I_e at AC-1, 400 V (EF001393)

70 A

Rated operation current I_e at AC-3, 400 V (EF001392)

40 A

Number of auxiliary contacts as normally closed contact (EF001377)

0

Number of auxiliary contacts as normally open contact (EF001376)

0

Number of normally closed contacts as main contact (EF001375)

0

Number of normally open contacts as main contact (EF001374)

4

Rated operation power at AC-3, 400 V (EF001364)

18.5 kW

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / BF40T4A23060 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.