

INDUSTRIAL COMPONENT DATA

**BF40T4A57560 LOVATO FOUR-POLE CONTACTOR, IEC
OPERATING CURRENT ITH (AC1) 70A, AC COIL 60HZ,
575VAC**

Brand: LOVATO ELECTRIC | Manufacturer Part Number: BF40T4A57560



Manufacturer	LOVATO ELECTRIC
MPN / Reference	BF40T4A57560
Catalog number	57560
Category	Power contactor, AC switching
Minimum order	1 Pcs
Document ID	EO-4A7DB7C0E7
Generated	2026-07-31

Product Overview

FOUR-POLE CONTACTOR, IEC OPERATING CURRENT ITH (AC1) = 70A, AC COIL 60HZ, 575VAC

4P CONTACTOR 70A AC1 575VAC 60HZ

Four-pole contactor, IEC operating current Ith (AC1) = 70A, AC coil 60Hz, 575VAC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LOVATO ELECTRIC > Industrial Contactors and Accessories - LOVATO ELECTRIC

Additional Product Information

BF40T4A57560

Four-pole contactor, IEC operating current Ith (AC1) = 70A, AC coil 60Hz, 575VAC

Technical specifications

Type of product:ContactorsNumber of poles:4Type of coil:AC coil 60HzRated coil voltage [V]:575IEC operating current Ith (AC1) [A]:70IEC operating current and power Ie (AC3) 400V [A/Kw]:40A /18.5KwUL/CSA horsepower ratings 480V [HP]:30Type of mounting:Screw / DIN rail 35mmOrder code BF40T4A57560

Weight [g] 1240

Qty. per package 1

Multiple qty. of packs per order 1

Package dimensions [mm] 141X080X120

Volume [cm³] 1354

Bar code [EAN13] 8013975222966
HS Code 85365080
ETIM for BF40T4A57560 Low-voltage industrial controls and switchgear (EC000066)
Feature Name
Feature Value
Voltage type for actuating (EF008242)
AC
Type of electrical connection of main circuit (EF006819)
Frame clamp
Rated control supply voltage AC 60 Hz (EF003979)
575 V
Modular version (EF001126)
No
Rated operation current I_e at AC-4, 400 V (EF008495)
24 A
Rated operation current I_e at AC-1, 400 V (EF001393)
70 A
Rated operation current I_e at AC-3, 400 V (EF001392)
40 A
Number of auxiliary contacts as normally closed contact (EF001377)
0
Number of auxiliary contacts as normally open contact (EF001376)
0
Number of normally closed contacts as main contact (EF001375)
0
Number of normally open contacts as main contact (EF001374)
4
Rated operation power at AC-3, 400 V (EF001364)
18.5 kW

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / BF40T4A57560 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.