

INDUSTRIAL COMPONENT DATA

KMH1L12 LOVATO LIMIT SWITCH, K SERIES, CERAMIC ROD LEVER, 1 BOTTOM CABLE ENTRY. DIMENSIONS TO EN 50047, META..

Brand: LOVATO ELECTRIC | Manufacturer Part Number: KMH1L12



Manufacturer	LOVATO ELECTRIC
MPN / Reference	KMH1L12
Catalog number	10000
Category	End switch
Minimum order	1 Pcs
Document ID	EO-16B348AA94
Generated	2026-08-05

Product Overview

LIMIT SWITCH, K SERIES, CERAMIC ROD LEVER, 1 BOTTOM CABLE ENTRY. DIMENSIONS TO EN 50047, METAL BODY, CONTACTS 1NO+2NC SLOW BREAK. CERAMIC ROD

CERAMIC LEVER METAL 1NO+2NC SLOW BREAK

Limit switch, K series, ceramic rod lever, 1 bottom cable entry. Dimensions to EN 50047, metal body, contacts 1NO+2NC slow action. Ceramic rod

K SERIES LIMIT SWITCH, LEVER WITH CERAMIC ROD, 1 BOTTOM ENTRY FOR CABLE. DIMENSIONS ACCORDING TO EN 50047, METAL HOUSING, SLOW 1NO+2NC CONTACTS. CERAMIC ROD

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	LOVATO ELECTRIC > Limit, micro and foot switches - LOVATO ELECTRIC
--------------	--

Additional Product Information

KMH1L12

Limit switch, K series, ceramic rod lever, 1 bottom cable entry. Dimensions to EN 50047, metal body, contacts 1NO+2NC slow action. Ceramic rod

Technical specifications

Type of product: Metal and plastic limit switches
Product characteristics: Ceramic rod lever
Housing material: Aluminium-zinc alloy
Rod characteristics: Ceramic
Type of contacts: 1NO+2NC Slow action
Cable entry: M20 on the bottom
Order code
KMH1L12

Weight [g] 212
Qty. per package 1
Multiple qty. of packs per order 1
Package dimensions [mm] 150X060X036
Volume [cm³] 324
Bar code [EAN13] 8013975116807
HS Code 85365080
76.14 £
ETIM for KMH1L12 Sensors (EC000030)
Feature Name
Feature Value
Alignment of the control element (EF008793)
Other
Type of interface (EF006977)
None
Type of control element (EF006976)
Actuating rod
Degree of protection (IP) (EF005474)
IP65
Construction type housing (EF004008)
Cuboid
Explosion safety category for dust (EF003998)
None
Explosion safety category for gas (EF003997)
None
Type of electric connection (EF003961)
Cable entry metrical
Type of interface for safety communication (EF003956)
None
Coating housing (EF001601)
Powder coated
Housing material (EF001596)
Metal
Switching function (EF000189)
Slow-action switch
Ambient temperature during operating (EF007515)
-25 °C
Switching function latching (EF007447)
No
Output electronic (EF006987)
No
Forced opening (EF006694)
Yes
With status indication (EF001602)
No
Suitable for safety functions (EF001597)
No

Number of contacts as change-over contact....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / KMH1L12 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.