

INDUSTRIAL COMPONENT DATA

KCH1L20 LOVATO LIMIT SWITCH, K SERIES, CERAMIC ROD LEVER, 2 SIDE CABLE ENTRY. DIMENSIONS COMPATIBLE TO EN 50..

Brand: LOVATO ELECTRIC | Manufacturer Part Number: KCH1L20



Manufacturer	LOVATO ELECTRIC
MPN / Reference	KCH1L20
Catalog number	10000
Category	End switch
Minimum order	1 Pcs
Document ID	EO-CEC0FFDCCF
Generated	2026-08-05

Product Overview

LIMIT SWITCH, K SERIES, CERAMIC ROD LEVER, 2 SIDE CABLE ENTRY. DIMENSIONS COMPATIBLE TO EN 50047, PLASTIC BODY, CONTACTS 2NO SLOW BREAK. CERAMIC ROD

CERAMIC ROD LEVER 2 ENTRIES L/S 2NO

Limit switch, K series, ceramic rod lever, 2 side cable entry. Dimensions compatible to EN 50047, plastic body, contacts 2NO slow action. Ceramic rod

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	LOVATO ELECTRIC > Limit, micro and foot switches - LOVATO ELECTRIC
--------------	--

Additional Product Information

KCH1L20

Limit switch, K series, ceramic rod lever, 2 side cable entry. Dimensions compatible to EN 50047, plastic body, contacts 2NO slow action. Ceramic rod

Technical specifications

Type of product: Metal and plastic limit switches Product characteristics: Ceramic rod lever Housing material: Polymer thermoplastic Rod characteristics: Ceramic Type of contacts: 2NO Slow action Cable entry: M20 on the sides Order code KCH1L20

Weight [g] 130

Qty. per package 1

Multiple qty. of packs per order 1
Package dimensions [mm] 150X060X036
Volume [cm³] 324
Bar code [EAN13] 8013975127506
HS Code 85365080
58.07 £
ETIM for KCH1L20 Sensors (EC000030)
Feature Name
Feature Value
Alignment of the control element (EF008793)
Other
Type of interface (EF006977)
None
Type of control element (EF006976)
Actuating rod
Degree of protection (IP) (EF005474)
IP65
Construction type housing (EF004008)
Cuboid
Explosion safety category for dust (EF003998)
None
Explosion safety category for gas (EF003997)
None
Type of electric connection (EF003961)
Cable entry metrical
Type of interface for safety communication (EF003956)
None
Coating housing (EF001601)
Other
Housing material (EF001596)
Plastic
Switching function (EF000189)
Slow-action switch
Ambient temperature during operating (EF007515)
-25 °C
Switching function latching (EF007447)
No
Output electronic (EF006987)
No
Forced opening (EF006694)
Yes
With status indication (EF001602)
No
Suitable for safety functions (EF001597)
No
Number of contacts as change-over contact (EF...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / KCH1L20 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.