

INDUSTRIAL COMPONENT DATA

CNM2020012 LOVATO MODULAR CONT. 1M 20A AC1 2P 12V MAN

Brand: LOVATO ELECTRIC | Manufacturer Part Number: CNM2020012



Manufacturer	LOVATO ELECTRIC
MPN / Reference	CNM2020012
Catalog number	2020012
Category	Installation contactor for distribution board
Minimum order	1 Pcs
Document ID	EO-B982BF407E
Generated	2026-08-02

Product Overview

MODULAR CONT. 1M 20A AC1 2P 12V MAN

Modular contactor with manual control, one or two-pole, 20A AC1, 12VAC/DC (1NO+1NC)

-

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LOVATO ELECTRIC > Modular contactors - LOVATO ELECTRIC

Additional Product Information

CNM2020012

Modular contactor with manual control, one or two-pole, 20A AC1, 12VAC/DC (1NO+1NC)

Technical specifications

Number of DIN modules:1Rated supply voltage:12V AC/DCIEC Conventional free air thermal current I_{th} [A]:20Order code

CNM2020012

Weight [g] 136

Qty. per package 10

Multiple qty. of packs per order 10

Package dimensions [mm] 178X090X072

Volume [cm³] 115.344

Bar code [EAN13] 8013975268339

HS Code 85365080

ETIM for CNM2020012 Modular devices for distribution board/surface mounting (EC001653)

Feature Name	
Feature Value	
Degree of protection (IP) (EF005474)	
IP20	
Voltage type (operating voltage) (EF005294)	
AC/DC	
Voltage type (excitation voltage) (EF005293)	
AC/DC	
Rated excitation voltage (EF008409)	
10.2 V	
Rated operating voltage (EF001435)	
12 V	
With day/night function (EF021124)	
No	
Hum-free (EF016334)	
Yes	
Additional equipment possible (EF008148)	
Yes	
Slider for hand switch (EF005240)	
Yes	
Number of contacts as normally open contact (EF008256)	
2	
Number of contacts as normally closed contact (EF008255)	
0	
Rated operation current (EF007679)	
20 A	
Max. load fluorescent lamp (parallel compensated) (EF004973)	
232 VA	
Max. load fluorescent lamp (Duo circuit) (EF004972)	
840 VA	
Max. load fluorescent lamp (EF004971)	
754 VA	
Max. incandescent lamp load (EF004952)	
2000 W	
Width in number of modular spacings (EF002950)	
1	
Built-in depth (EF000218)	
65 mm	

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / CNM2020012 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.