

INDUSTRIAL COMPONENT DATA

31RC8048 RC8048 LOVATO EARTH LEAKAGE RELAY WITH 1 OPERATION THRESHOLD, COMPACT PANEL MOUNT. CT INCORPORATED,..

Brand: LOVATO ELECTRIC | Manufacturer Part Number: 31RC8048



Manufacturer	LOVATO ELECTRIC
MPN / Reference	31RC8048
Catalog number	RC8048
Category	Residual current monitoring relay
Minimum order	1 Pcs
Document ID	EO-B76A7C6B8B
Generated	2026-08-02

Product Overview

EARTH LEAKAGE RELAY WITH 1 OPERATION THRESHOLD, COMPACT PANEL MOUNT. CT INCORPORATED, 24-48VAC/DC

Diff relay. + toroidal 80mm 24-48V AC/DC

Earth leakage relay with 1 operatin threshold, compact panel mount. CT incorporated, 24-48VAC/DC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LOVATO ELECTRIC > Earth leakage relays - LOVATO ELECTRIC

Additional Product Information

31RC8048

Earth leakage relay with 1 operatin threshold, compact panel mount. CT incorporated, 24-48VAC/DC

Technical specifications

Type of product:Earth leakage relaysResidual operation characteristic:Type AType of installation:Internal panel mountingToroidal transformer:Incorporated diam. 80mm/3.15"N° of operating threshold:1Rated supply voltage:24-48VAC/DCOrder code 31RC8048

Weight [g] 585.9

Qty. per package 1

Multiple qty. of packs per order 1

Package dimensions [mm] 170X175X086

Volume [cm³] 2558.5
Bar code [EAN13] 8013975064238
HS Code 85389091
468.57 £
ETIM for 31RC8048 Relays (EC001445)
Feature Name
Feature Value
Type of electric connection (EF003961)
Screw connection
Function (EF000030)
For AC-current system
Response value amperage 1 (EF008204)
25 mA
Indication of difference current (EF003424)
Yes
Error registration possible (EF003423)
Yes
With detachable clamps (EF003340)
No
Number of contacts as change-over contact (EF008257)
1
Number of contacts as normally open contact (EF008256)
0
Number of contacts as normally closed contact (EF008255)
0
Min. adjustable delay-on energization time (EF008190)
0.02 s
Max. permitted delay-on energization time (EF008189)
5 s
Depth (EF000049)
70 mm
Height (EF000040)
160 mm
Width (EF000008)
150 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / 31RC8048 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.