

INDUSTRIAL COMPONENT DATA

M1R00912230A7 LOVATO DIRECT-ON-LINE-STARTER, ENCLOSED WITH THERMAL OVERLOAD RELAY, WITH RESET PUSH BUTTON, W..

Brand: LOVATO ELECTRIC | Manufacturer Part Number: M1R00912230A7



Manufacturer	LOVATO ELECTRIC
MPN / Reference	M1R00912230A7
Catalog number	00912230
Category	Motor starter/Motor starter combination
Minimum order	1 Pcs
Document ID	EO-288D51F9BE
Generated	2026-08-02

Product Overview

DIRECT-ON-LINE-STARTER, ENCLOSED WITH THERMAL OVERLOAD RELAY, WITH RESET PUSH BUTTON, WITH BF09/BF18 CONTACTOR, 10A MAX (3...4KW AT 400V), IP65. CONTACTOR COIL VOLTAGE 230VAC 50/60HZ
DOL STARTER M1R 230/50-60 2,5-4A

Direct-on-line-starter, enclosed with thermal overload relay, with RESET pushbutton, with BF09/BF18 contactor, 10A max (3...4kW at 400V), IP65. Contactor coil voltage 230VAC 50/60Hz

DIRECT STARTER, WITH THERMAL RELAY IN INSULATED CASE, WITH RESET BUTTON, WITH BF09/BF18 CONTACTOR, 10A MAX (3...4KW AT 400V), IP65. CONTACTOR COIL VOLTAGE 230VAC 50/60HZ

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	LOVATO ELECTRIC > Electromechanical starters - LOVATO ELECTRIC
--------------	--

Additional Product Information

M1R00912230A7

Direct-on-line-starter, enclosed with thermal overload relay, with RESET pushbutton, with BF09/BF18 contactor, 10A max (3...4kW at 400V), IP65. Contactor coil voltage 230VAC 50/60Hz

Technical specifications

Type of product:Direct-on-line-startersIEC operating current and power Ie (AC3) 400V [A/Kw]:4A / 1.5kWUL/CSA

horsepower ratings 480V [HP]:2Type:Enclosed with thermal overload relayType of coil:AC coilType of pushbutton:With reset push buttonContactor coil voltage:230VAC 50/60HZOrder code M1R00912230A7

Weight [g] 980
Qty. per package 1
Multiple qty. of packs per order 1
Package dimensions [mm] 206X092X170
Volume [cm³] 3221.84
Bar code [EAN13] 8013975158425
HS Code 85371098
193.44 £
ETIM for M1R00912230A7 Low-voltage industrial controls and switchgear (EC001037)
Feature Name
Feature Value
Type of motor starter (EF009598)
Direct starter
Voltage type for actuating (EF008242)
AC
Type of electrical connection for auxiliary- and control current circuit (EF006979)
Screw connection
Type of electrical connection of main circuit (EF006819)
Screw connection
Release class (EF006668)
CLASS 10 A
Degree of protection (IP) (EF005474)
IP65
Rated control supply voltage AC 60 Hz (EF003979)
230 V
Rated control supply voltage AC 50 Hz (EF003978)
230 V
Overload release current setting (EF002336)
2.5 A
Temperature compensated overload protection (EF009604)
Yes
Supporting protocol for SafetyBUS p (EF007527)
No
Supporting protocol for PROFIsafe (EF007526)
No
Supporting protocol for P...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / M1R00912230A7 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.