

INDUSTRIAL COMPONENT DATA

M1P00912400A5 LOVATO DIRECT-ON-LINE-STARTER, ENCLOSED WITH THERMAL OVERLOAD RELAY, WITH START AND STOP/RESET..

Brand: LOVATO ELECTRIC | Manufacturer Part Number: M1P00912400A5



Manufacturer	LOVATO ELECTRIC
MPN / Reference	M1P00912400A5
Catalog number	00912400
Category	Motor starter/Motor starter combination
Minimum order	1 Pcs
Document ID	EO-3E2B272FC8
Generated	2026-08-04

Product Overview

DIRECT-ON-LINE-STARTER, ENCLOSED WITH THERMAL OVERLOAD RELAY, WITH START AND STOP/RESET BUTTONS, WITH BF09/BF18 CONTACTOR, 6.5A MAX (2.2...3KW AT 400V), IP65. CONTACTOR COIL VOLTAGE 400VAC 50/60HZ

DOL STARTER M1P 400/50-60 1-1V6A

Direct-on-line-starter, 1...1.6A (0.37...0.55kW at 400V), IP65, contactor coil voltage 400VAC 50/60Hz, non-metallic enclosure, with thermal overload relay, with START and STOP/RESET buttons

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LOVATO ELECTRIC > Electromechanical starters - LOVATO ELECTRIC

Additional Product Information

M1P00912400A5

Direct-on-line-starter, 1...1.6A (0.37...0.55kW at 400V), IP65, contactor coil voltage 400VAC 50/60Hz, non-metallic enclosure, with thermal overload relay, with START and STOP/RESET buttons

Technical specifications

Type of product:Direct-on-line-startersIEC operating current and power Ie (AC3) 400V [A/Kw]:1.6A / 0.55kWUL/CSA horsepower ratings 480V [HP]:0.75Type:Enclosed with thermal overload relayType of coil:AC coilType of pushbutton:With Start-Stop/Reset buttonsContactor coil voltage:400VAC 50/60HZOrder code M1P00912400A5

Weight [g] 1036

Qty. per package 1
Multiple qty. of packs per order 1
Package dimensions [mm] 206X092X170
Volume [cm³] 3221.84
Bar code [EAN13] 8013975149737
HS Code 85371098
210.33 £
ETIM for M1P00912400A5 Low-voltage industrial controls and switchgear (EC001037)
Feature Name
Feature Value
Degree of protection (NEMA) (EF011959)
4X
Type of motor starter (EF009598)
Direct starter
Voltage type for actuating (EF008242)
AC
Type of electrical connection for auxiliary- and control current circuit (EF006979)
Screw connection
Type of electrical connection of main circuit (EF006819)
Screw connection
Release class (EF006668)
CLASS 10 A
Degree of protection (IP) (EF005474)
IP65
Rated control supply voltage AC 60 Hz (EF003979)
400 V
Rated control supply voltage AC 50 Hz (EF003978)
400 V
Overload release current setting (EF002336)
1 A
Temperature compensated overload protection (EF009604)
Yes
Supporting protocol for SafetyBUS p (EF007527)
No
Supporting pr...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / M1P00912400A5 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.