

INDUSTRIAL COMPONENT DATA

M2P02512230B2 LOVATO DIRECT-ON-LINE-STARTER, ENCLOSED WITH THERMAL OVERLOAD RELAY, WITH START AND STOP/RESET..

Brand: LOVATO ELECTRIC | Manufacturer Part Number: M2P02512230B2



Manufacturer	LOVATO ELECTRIC
MPN / Reference	M2P02512230B2
Catalog number	02512230
Category	Motor starter/Motor starter combination
Minimum order	1 Pcs
Document ID	EO-6A12028AF9
Generated	2026-08-05

Product Overview

DIRECT-ON-LINE-STARTER, ENCLOSED WITH THERMAL OVERLOAD RELAY, WITH START AND STOP/RESET BUTTONS, WITH BF25/BF32 CONTACTOR, 23A MAX (11KW AT 400V), IP65. CONTACTOR COIL VOLTAGE 230VAC 50/60HZ

DOL STARTER M2P 230/50-60 17-23A

Direct-on-line-starter, 17...23A (11kW at 400V), IP65, contactor coil voltage 230VAC 50/60Hz, non-metallic enclosure, with thermal overload relay, with START and STOP/RESET buttons

DIRECT STARTER, 17...23A (11KW AT 400V), CONTACTOR COIL VOLTAGE 230VAC 50/60HZ, WITH THERMAL RELAY IN IP65 INSULATED ENCLOSURE, WITH START AND STOP/RESET BUTTONS,

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	LOVATO ELECTRIC > Electromechanical starters - LOVATO ELECTRIC
--------------	--

Additional Product Information

M2P02512230B2

Direct-on-line-starter, 17...23A (11kW at 400V), IP65, contactor coil voltage 230VAC 50/60Hz, non-metallic enclosure, with thermal overload relay, with START and STOP/RESET buttons

Technical specifications

Type of product:Direct-on-line-startersIEC operating current and power Ie (AC3) 400V [A/Kw]:23A / 11kWUL/CSA

horsepower ratings 480V [HP]:15Type:Enclosed with thermal overload relayType of coil:AC coilType of pushbutton:With

Start-Stop/Reset buttons Contactor coil voltage: 230VAC 50/60HZ Order code M2P02512230B2

Weight [g] 1220

Qty. per package 1

Multiple qty. of packs per order 1

Package dimensions [mm] 238X114X188

Volume [cm³] 5100.816

Bar code [EAN13] 8013975158227

HS Code 85371098

302.85 £

ETIM for M2P02512230B2 Low-voltage industrial controls and switchgear (EC001037)

Feature Name

Feature Value

Degree of protection (NEMA) (EF011959)

4X

Type of motor starter (EF009598)

Direct starter

Voltage type for actuating (EF008242)

AC

Type of electrical connection for auxiliary- and control current circuit (EF006979)

Screw connection

Type of electrical connection of main circuit (EF006819)

Screw connection

Release class (EF006668)

CLASS 10 A

Degree of protection (IP) (EF005474)

IP65

Rated control supply voltage AC 60 Hz (EF003979)

230 V

Rated control supply voltage AC 50 Hz (EF003978)

230 V

Overload release current setting (EF002336)

17 A

Temperature compensated overload protection (EF009604)

Yes

Supporting protocol for SafetyBUS p (EF007527)

No

Supporting protocol for...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / M2P02512230B2 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.