

INDUSTRIAL COMPONENT DATA

M2P02512400B2 LOVATO DIRECT-ON-LINE-STARTER, ENCLOSED WITH THERMAL OVERLOAD RELAY, WITH START AND STOP/RESET..

Brand: LOVATO ELECTRIC | Manufacturer Part Number: M2P02512400B2



Manufacturer	LOVATO ELECTRIC
MPN / Reference	M2P02512400B2
Catalog number	02512400
Category	Motor starter/Motor starter combination
Minimum order	1 Pcs
Document ID	EO-EBDA7C5BF8
Generated	2026-08-03

Product Overview

DIRECT-ON-LINE-STARTER, ENCLOSED WITH THERMAL OVERLOAD RELAY, WITH START AND STOP/RESET BUTTONS, WITH BF25/BF32 CONTACTOR, 23A MAX (11KW AT 400V), IP65. CONTACTOR COIL VOLTAGE 400VAC 50/60HZ

DOL STARTER M2P 400/50-60 17-23A

Direct-on-line-starter, 17...23A (11kW at 400V), IP65, contactor coil voltage 400VAC 50/60Hz, non-metallic enclosure, with thermal overload relay, with START and STOP/RESET buttons

DIRECT STARTER, 17...23A (11KW AT 400V), CONTACTOR COIL VOLTAGE 400VAC 50/60HZ, WITH THERMAL RELAY IN IP65 INSULATED CASE, WITH START AND STOP/RESET BUTTONS,

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	LOVATO ELECTRIC > Electromechanical starters - LOVATO ELECTRIC
--------------	--

Additional Product Information

M2P02512400B2

Direct-on-line-starter, 17...23A (11kW at 400V), IP65, contactor coil voltage 400VAC 50/60Hz, non-metallic enclosure, with thermal overload relay, with START and STOP/RESET buttons

Technical specifications

Type of product:Direct-on-line-startersIEC operating current and power Ie (AC3) 400V [A/Kw]:23A / 11kWUL/CSA

horsepower ratings 480V [HP]:15Type:Enclosed with thermal overload relayType of coil:AC coilType of pushbutton:With

Start-Stop/Reset buttons Contactor coil voltage: 400VAC 50/60HZ Order code M2P02512400B2

Weight [g] 1232

Qty. per package 1

Multiple qty. of packs per order 1

Package dimensions [mm] 238X114X188

Volume [cm³] 5100.816

Bar code [EAN13] 8013975151846

HS Code 85371098

302.85 £

ETIM for M2P02512400B2 Low-voltage industrial controls and switchgear (EC001037)

Feature Name

Feature Value

Type of electrical connection for auxiliary- and control current circuit (EF006979)

Screw connection

Type of electrical connection of main circuit (EF006819)

Screw connection

Release class (EF006668)

CLASS 10 A

Degree of protection (IP) (EF005474)

IP65

Rated control supply voltage AC 60 Hz (EF003979)

400 V

Rated control supply voltage AC 50 Hz (EF003978)

400 V

Overload release current setting (EF002336)

17 A

Temperature compensated overload protection (EF009604)

Yes

Supporting protocol for SafetyBUS p (EF007527)

No

Supporting protocol for PROFIsafe (EF007526)

No

Supporting protocol for PROFINET IO (EF007525)

No

Supporting protocol for PROFINET CBA (EF007524)

No

Suppo...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / M2P02512400B2 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.