

INDUSTRIAL COMPONENT DATA

M3P05012024B6 LOVATO DIRECT-ON-LINE-STARTER, ENCLOSED WITH THERMAL OVERLOAD RELAY, WITH START AND STOP/RESET..

Brand: LOVATO ELECTRIC | Manufacturer Part Number: M3P05012024B6



Manufacturer	LOVATO ELECTRIC
MPN / Reference	M3P05012024B6
Catalog number	05012024
Category	Motor starter/Motor starter combination
Minimum order	1 Pcs
Document ID	EO-668E3C4377
Generated	2026-08-05

Product Overview

DIRECT-ON-LINE-STARTER, ENCLOSED WITH THERMAL OVERLOAD RELAY, WITH START AND STOP/RESET BUTTONS, WITH BF38/BF50/BF65/BF80/BF95 CONTACTOR, 50A MAX (22KW AT 400V), IP65. CONTACTOR COIL VOLTAGE 24VAC 50/60HZ

DOL STARTER M3P 24/50-60 50A

Direct-on-line-starter, 35...50A (18.5...22kW at 400V), IP65, contactor coil voltage 24VAC 50/60Hz, non-metallic enclosure, with thermal overload relay, with START and STOP/RESET buttons

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LOVATO ELECTRIC > Electromechanical starters - LOVATO ELECTRIC

Additional Product Information

M3P05012024B6

Direct-on-line-starter, 35...50A (18.5...22kW at 400V), IP65, contactor coil voltage 24VAC 50/60Hz, non-metallic enclosure, with thermal overload relay, with START and STOP/RESET buttons

Technical specifications

Type of product:Direct-on-line-startersIEC operating current and power Ie (AC3) 400V [A/Kw]:50A / 22kWUL/CSA

horsepower ratings 480V [HP]:40Type:Enclosed with thermal overload relayType of coil:AC coilType of pushbutton:With

Start-Stop/Reset buttonsContactor coil voltage:24VAC 50/60HZOrder code M3P05012024B6

Weight [g] 3940

Qty. per package 1
Multiple qty. of packs per order 1
Package dimensions [mm] 295X240X225
Volume [cm³] 15930
Bar code [EAN13] 8013975183571
HS Code 85371098
726.25 £
ETIM for M3P05012024B6 Low-voltage industrial controls and switchgear (EC001037)
Feature Name
Feature Value
Degree of protection (NEMA) (EF011959)
4X
Type of motor starter (EF009598)
Direct starter
Voltage type for actuating (EF008242)
AC
Type of electrical connection for auxiliary- and control current circuit (EF006979)
Screw connection
Type of electrical connection of main circuit (EF006819)
Screw connection
Release class (EF006668)
CLASS 10 A
Degree of protection (IP) (EF005474)
IP65
Rated control supply voltage AC 60 Hz (EF003979)
24 V
Rated control supply voltage AC 50 Hz (EF003978)
24 V
Overload release current setting (EF002336)
35 A
Temperature compensated overload protection (EF009604)
Yes
Supporting protocol for SafetyBUS p (EF007527)
No
Supporting protocol for...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / M3P05012024B6 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.