

INDUSTRIAL COMPONENT DATA

M0P009120241 LOVATO DIRECT-ON-LINE-STARTER, ENCLOSED WITH THERMAL OVERLOAD RELAY, WITH START AND STOP/RESET ..

Brand: LOVATO ELECTRIC | Manufacturer Part Number: M0P009120241



Manufacturer	LOVATO ELECTRIC
MPN / Reference	M0P009120241
Catalog number	009120241
Category	Motor starter/Motor starter combination
Minimum order	1 Pcs
Document ID	EO-8E084716FC
Generated	2026-08-04

Product Overview

DIRECT-ON-LINE-STARTER, ENCLOSED WITH THERMAL OVERLOAD RELAY, WITH START AND STOP/RESET BUTTONS, WITH BG09/BG12 CONTACTOR, 1A MAX (0.18...0.25KW AT 400V), IP65. CONTACTOR COIL VOLTAGE 24VAC 50/60HZ

DOL STARTER M0P 24/50-60 0,6-1A

Direct-on-line-starter, 0.6...1A (0.18...0.25kW at 400V), IP65, contactor coil voltage 24VAC 50/60Hz, non-metallic enclosure, with thermal overload relay, with START and STOP/RESET buttons

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LOVATO ELECTRIC > Electromechanical starters - LOVATO ELECTRIC

Additional Product Information

M0P009120241

Direct-on-line-starter, 0.6...1A (0.18...0.25kW at 400V), IP65, contactor coil voltage 24VAC 50/60Hz, non-metallic enclosure, with thermal overload relay, with START and STOP/RESET buttons

Technical specifications

Type of product:Direct-on-line-startersIEC operating current and power I_e (AC3) 400V [A/Kw]:1A / 0.25kWUL/CSA

horsepower ratings 480V [HP]:7.5Type:Enclosed with thermal overload relayType of coil:AC coilType of pushbutton:With

Start-Stop/Reset buttonsContactor coil voltage:24VAC 50/60HZOrder code M0P009120241

Weight [g] 730.4

Qty. per package 1
Multiple qty. of packs per order 1
Package dimensions [mm] 187X092X160
Volume [cm³] 2752.64
Bar code [EAN13] 8013975205129
HS Code 85371098
ETIM for M0P009120241 Low-voltage industrial controls and switchgear (EC001037)
Feature Name
Feature Value
Degree of protection (NEMA) (EF011959)
4X
Type of motor starter (EF009598)
Direct starter
Voltage type for actuating (EF008242)
AC
Type of electrical connection for auxiliary- and control current circuit (EF006979)
Screw connection
Type of electrical connection of main circuit (EF006819)
Screw connection
Release class (EF006668)
CLASS 10 A
Degree of protection (IP) (EF005474)
IP65
Rated control supply voltage AC 60 Hz (EF003979)
24 V
Rated control supply voltage AC 50 Hz (EF003978)
24 V
Overload release current setting (EF002336)
0.6 A
Temperature compensated overload protection (EF009604)
Yes
Supporting protocol for SafetyBUS p (EF007527)
No
Supporting protocol for PRO...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / M0P009120241 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.