

INDUSTRIAL COMPONENT DATA

M0P009122301V5 LOVATO DIRECT-ON-LINE-STARTER, ENCLOSED WITH THERMAL OVERLOAD RELAY, WITH START AND STOP/RESE..

Brand: LOVATO ELECTRIC | Manufacturer Part Number: M0P009122301V5



Manufacturer	LOVATO ELECTRIC
MPN / Reference	M0P009122301V5
Catalog number	009122301
Category	Motor starter/Motor starter combination
Minimum order	1 Pcs
Document ID	EO-E0AF9DB655
Generated	2026-08-04

Product Overview

DIRECT-ON-LINE-STARTER, ENCLOSED WITH THERMAL OVERLOAD RELAY, WITH START AND STOP/RESET BUTTONS, WITH BG09/BG12 CONTACTOR, 1.5A MAX (0.37KW A 400V), IP65. CONTACTOR COIL VOLTAGE 230VAC 50/60HZ

DOL STARTER M0P 230/50-60 0,9-1,5A

Direct-on-line-starter, 0.9...1.5A (0.37kW at 400V), IP65, contactor coil voltage 230VAC 50/60Hz, non-metallic enclosure, with thermal overload relay, with START and STOP/RESET buttons

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LOVATO ELECTRIC > Electromechanical starters - LOVATO ELECTRIC

Additional Product Information

M0P009122301V5

Direct-on-line-starter, 0.9...1.5A (0.37kW at 400V), IP65, contactor coil voltage 230VAC 50/60Hz, non-metallic enclosure, with thermal overload relay, with START and STOP/RESET buttons

Technical specifications

Type of product:Direct-on-line-startersIEC operating current and power I_e (AC3) 400V [A/Kw]:1.5A / 0.37kWUL/CSA horsepower ratings 480V [HP]:0.75Type:Enclosed with thermal overload relayType of coil:AC coilType of pushbutton:With Start-Stop/Reset buttonsContactor coil voltage:230VAC 50/60HZOrder code M0P009122301V5

Weight [g] 760

Qty. per package 1
Multiple qty. of packs per order 1
Package dimensions [mm] 187X092X160
Volume [cm³] 2752.64
Bar code [EAN13] 8013975155851
HS Code 85371098
203.77 £
ETIM for M0P009122301V5 Low-voltage industrial controls and switchgear (EC001037)
Feature Name
Feature Value
Degree of protection (NEMA) (EF011959)
4X
Type of motor starter (EF009598)
Direct starter
Voltage type for actuating (EF008242)
AC
Type of electrical connection for auxiliary- and control current circuit (EF006979)
Screw connection
Type of electrical connection of main circuit (EF006819)
Screw connection
Release class (EF006668)
CLASS 10 A
Degree of protection (IP) (EF005474)
IP65
Rated control supply voltage AC 60 Hz (EF003979)
230 V
Rated control supply voltage AC 50 Hz (EF003978)
230 V
Overload release current setting (EF002336)
0.9 A
Temperature compensated overload protection (EF009604)
Yes
Supporting protocol for SafetyBUS p (EF007527)
No
Supporting pro...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / M0P009122301V5 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.