

INDUSTRIAL COMPONENT DATA

DM35T0400 LOVATO CT 400/5A 80X10, 60X30, 50X50MM BUSBAR

Brand: LOVATO ELECTRIC | Manufacturer Part Number: DM35T0400



Manufacturer	LOVATO ELECTRIC
MPN / Reference	DM35T0400
Catalog number	10000
Category	Current transformer
Minimum order	1 Pcs
Document ID	EO-36A25BFF93
Generated	2026-08-04

Product Overview

CT 400/5A 80X10, 60X30, 50X50MM BUSBAR

Current transformer, solid-core, for Ø66mm cable. For 80X12.5mm, 60X30mm, 50X50mm busbars, 400A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **LOVATO ELECTRIC > Metering instruments and current transformers - LOVATO ELECTRIC**

Additional Product Information

Order code DM35T0400

Weight [g]

Qty. per package 1

Multiple qty. of packs per order 1

Package dimensions [mm]

Volume [cm³]

Bar code [EAN13] 8013975243251

HS Code 85043180

Dimensions

Certifications:

EAC

GOST Compliance:

IEC/EN/BS 61869-2

IEC/EN/BS 61869-1 Product designation Current transformers

Product type designation DM35T0400

Auxiliary supply Us

Operational frequency

min Hz 50

max Hz 60

Current inputs

Primary current I_{pn} (/5) A 400

Secondary output current A 5

Overload withstand I_{pn} % 120

Insulations

Rated insulation voltage U_i IEC/EN V 720

IEC rated short-time thermal current I_{th} I_{th} for s 40...60

IEC rated dynamic current I_{dyn} I_{th} for s 2.5

Insulation dry type Class E

Mechanical features

Terminals type Screw

Fixing DIN rail or by Screw

Ambient conditions

Temperature

Operating temperature

min °C -25

max °C +50

Storage temperature

min °C -40

max °C +80

Relative humidity % 90

Protection degree IP30

ETIM classification

ETIM 8.0 EC002048 - Current transformer

ETIM for DM35T0400 Low-voltage industrial controls and switchgear (EC002048)

Feature Name

Feature Value

Secondary connection (EF021093)

Screw connection

Accuracy class (EF008842)

1

Overcurrent limiting factor (EF007511)

FS 5

Model (EF000010)

Other

Width opening (EF012758)

30 mm

Height opening (EF012757)

60 mm

Calibrated (EF008836)

No

With contact protection (EF008186)

No
Snap mounting (EF007462)
Yes
With copper rail (EF007380)
No
Rated secondary current (EF007471)
5 A
Rated secondary apparent power (EF007470)
5 VA
Rated pr...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / DM35T0400 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.