

INDUSTRIAL COMPONENT DATA

M1P01810110 LOVATO DIRECT-ON-LINE-STARTER, ENCLOSED WITHOUT THERMAL OVERLOAD RELAY, WITH START AND STOP/RESE..

Brand: LOVATO ELECTRIC | Manufacturer Part Number: M1P01810110



Manufacturer	LOVATO ELECTRIC
MPN / Reference	M1P01810110
Catalog number	10000
Category	Motor starter/Motor starter combination
Minimum order	1 Pcs
Document ID	EO-ACF1D86B06
Generated	2026-08-04

Product Overview

DIRECT-ON-LINE-STARTER, ENCLOSED WITHOUT THERMAL OVERLOAD RELAY, WITH START AND STOP/RESET BUTTONS, WITH BF09/BF18 CONTACTOR, 18A MAX. ($\leq 440V$), IP65. CONTACTOR COIL VOLTAGE 110VAC 50/60HZ DOL STARTER M1P 110/50-60 18A W/O RELAY

Direct-on-line-starter, enclosed without thermal overload relay, with START and STOP/RESET buttons, with BF09/BF18 contactor, 18A max ($\leq 440V$), IP65. Contactor coil voltage 110VAC 50/60Hz

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	LOVATO ELECTRIC > Electromechanical starters - LOVATO ELECTRIC
--------------	--

Additional Product Information

M1P01810110

Direct-on-line-starter, enclosed without thermal overload relay, with START and STOP/RESET buttons, with BF09/BF18 contactor, 18A max ($\leq 440V$), IP65. Contactor coil voltage 110VAC 50/60Hz

Technical specifications

Type of product:Direct-on-line-startersUL/CSA horsepower ratings 480V [HP]:10Type:Enclosed without thermal overload relayType of coil:AC coilType of pushbutton:With Start-Stop/Reset buttonsContactor coil voltage:110VAC 50/60HZOrder code M1P01810110

Weight [g] 910

Qty. per package 1

Multiple qty. of packs per order 1
Package dimensions [mm] 206X092X170
Volume [cm³] 3221.84
Bar code [EAN13] 8013975183359
HS Code 85371098
154.28 £
ETIM for M1P01810110 Low-voltage industrial controls and switchgear (EC001037)
Feature Name
Feature Value
Degree of protection (NEMA) (EF011959)
4X
Type of motor starter (EF009598)
Direct starter
Voltage type for actuating (EF008242)
AC
Type of electrical connection for auxiliary- and control current circuit (EF006979)
Screw connection
Type of electrical connection of main circuit (EF006819)
Screw connection
Release class (EF006668)
CLASS 10 A
Degree of protection (IP) (EF005474)
IP65
Rated control supply voltage AC 60 Hz (EF003979)
110 V
Rated control supply voltage AC 50 Hz (EF003978)
110 V
Temperature compensated overload protection (EF009604)
Yes
Supporting protocol for SafetyBUS p (EF007527)
No
Supporting protocol for PROFIsafe (EF007526)
No
Supporting protocol for PROFINET IO (EF007525)
No
Supporting protocol for PROFINET CBA...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / M1P01810110 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.