

**INDUSTRIAL COMPONENT DATA**

# M1P01810024 LOVATO direct starter without relay box with pushbutton start and stop / reset 18A 24V AC

Brand: LOVATO ELECTRIC | Manufacturer Part Number: M1P01810024



|                 |                                         |
|-----------------|-----------------------------------------|
| Manufacturer    | LOVATO ELECTRIC                         |
| MPN / Reference | M1P01810024                             |
| Catalog number  | 10000                                   |
| Category        | Motor starter/Motor starter combination |
| Minimum order   | 1 Pcs                                   |
| Document ID     | EO-18B426085C                           |
| Generated       | 2026-08-05                              |

## Product Overview

direct starter without relay box with pushbutton start and stop / reset 18A 24V AC

DOL STARTER M1P 24/50-60 18A W/O RELAY

Direct-on-line-starter, enclosed without thermal overload relay, with START and STOP/RESET buttons, with BF09/BF18 contactor, 18A max ( $\leq 440V$ ), IP65. Contactor coil voltage 24VAC 50/60Hz

DIRECT STARTER, 18A (5.5KW AT 400V), CONTACTOR COIL VOLTAGE 460VAC 50/60HZ, WITH THERMAL RELAY IN IP65 INSULATED ENCLOSURE, WITH START AND STOP/RESET BUTTONS,

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                                                |
|--------------|----------------------------------------------------------------|
| Catalog path | LOVATO ELECTRIC > Electromechanical starters - LOVATO ELECTRIC |
|--------------|----------------------------------------------------------------|

## Additional Product Information

M1P01810024

Direct-on-line-starter, enclosed without thermal overload relay, with START and STOP/RESET buttons, with BF09/BF18 contactor, 18A max ( $\leq 440V$ ), IP65. Contactor coil voltage 24VAC 50/60Hz

Technical specifications

Type of product:Direct-on-line-startersUL/CSA horsepower ratings 480V [HP]:10Type:Enclosed without thermal overload relayType of coil:AC coilOrder code M1P01810024

Weight [g] 900

Qty. per package 1

Multiple qty. of packs per order 1

Package dimensions [mm] 206X092X170

Volume [cm<sup>3</sup>] 3221.84  
Bar code [EAN13] 8013975207260  
HS Code 85371098  
ETIM for M1P01810024 Low-voltage industrial controls and switchgear (EC001037)  
Feature Name  
Feature Value  
Degree of protection (NEMA) (EF011959)  
4X  
Type of motor starter (EF009598)  
Direct starter  
Voltage type for actuating (EF008242)  
AC  
Type of electrical connection for auxiliary- and control current circuit (EF006979)  
Screw connection  
Type of electrical connection of main circuit (EF006819)  
Screw connection  
Release class (EF006668)  
CLASS 10 A  
Degree of protection (IP) (EF005474)  
IP65  
Rated control supply voltage AC 60 Hz (EF003979)  
24 V  
Rated control supply voltage AC 50 Hz (EF003978)  
24 V  
Temperature compensated overload protection (EF009604)  
Yes  
Supporting protocol for SafetyBUS p (EF007527)  
No  
Supporting protocol for PROFIsafe (EF007526)  
No  
Supporting protocol for PROFINET IO (EF007525)  
No  
Supporting protocol for PROFINET CBA (EF007524)  
No  
Supporting protocol for Foundation Fieldbus (EF007522)  
No  
Supporting protocol for....

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / M1P01810024 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.