

INDUSTRIAL COMPONENT DATA

M3P06510110 LOVATO DIRECT-ON-LINE-STARTER, ENCLOSED WITHOUT THERMAL OVERLOAD RELAY, WITH START AND STOP/RESE..

Brand: LOVATO ELECTRIC | Manufacturer Part Number: M3P06510110



Manufacturer	LOVATO ELECTRIC
MPN / Reference	M3P06510110
Catalog number	10000
Category	Motor starter/Motor starter combination
Minimum order	1 Pcs
Document ID	EO-F2AAB8F9EA
Generated	2026-08-03

Product Overview

DIRECT-ON-LINE-STARTER, ENCLOSED WITHOUT THERMAL OVERLOAD RELAY, WITH START AND STOP/RESET BUTTONS, WITH BF50/BF65/BF80/BF95 CONTACTOR, 50A MAX. ($\leq 440V$), IP65. CONTACTOR COIL VOLTAGE 110VAC 50/60HZ

DOL STARTER M3P 110/50-60 65A

Direct-on-line-starter, enclosed without thermal overload relay, with START and STOP/RESET buttons, with BF50/BF65/BF80/BF95 contactor, 50A max ($\leq 440V$), IP65. Contactor coil voltage 110VAC 50/60Hz

DIRECT STARTER, WITHOUT THERMAL RELAY IN INSULATED CASE, WITH START AND STOP/RESET BUTTONS, WITH CONTACTOR BF50/BF65/BF80/BF95, 50A MAX. ($\leq 440V$), IP65. CONTACTOR COIL VOLTAGE 110VAC 50/60HZ

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	LOVATO ELECTRIC > Electromechanical starters - LOVATO ELECTRIC
--------------	--

Additional Product Information

M3P06510110

Direct-on-line-starter, enclosed without thermal overload relay, with START and STOP/RESET buttons, with BF50/BF65/BF80/BF95 contactor, 50A max ($\leq 440V$), IP65. Contactor coil voltage 110VAC 50/60Hz

Technical specifications

Type of product:Direct-on-line-startersUL/CSA horsepower ratings 480V [HP]:50Type:Enclosed without thermal overload relayType of coil:AC coilType of pushbutton:With Start-Stop/Reset buttonsContactor coil voltage:110VAC 50/60HZOrder

code M3P06510110

Weight [g] 3420

Qty. per package 1

Multiple qty. of packs per order 1

Package dimensions [mm] 295X240X225

Volume [cm³] 15930

Bar code [EAN13] 8013975211311

HS Code 85371098

ETIM for M3P06510110 Low-voltage industrial controls and switchgear (EC001037)

Feature Name

Feature Value

Degree of protection (NEMA) (EF011959)

4X

Type of motor starter (EF009598)

Direct starter

Voltage type for actuating (EF008242)

AC

Type of electrical connection for auxiliary- and control current circuit (EF006979)

Screw connection

Type of electrical connection of main circuit (EF006819)

Screw connection

Release class (EF006668)

CLASS 10 A

Degree of protection (IP) (EF005474)

IP65

Rated control supply voltage AC 60 Hz (EF003979)

110 V

Rated control supply voltage AC 50 Hz (EF003978)

110 V

Temperature compensated overload protection (EF009604)

Yes

Supporting protocol for SafetyBUS p (EF007527)

No

Supporting protocol for PROFIsafe (EF007526)

No

Supporting protocol for PROFINET IO (EF007525)

No

Supporting protocol for PROFINET CBA...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / M3P06510110 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.