

INDUSTRIAL COMPONENT DATA

R4D415 LOVATO EARTH LEAKAGE RELAY WITH 2 OPERATION THRESHOLDS, FLUSH MOUNT. EXTERNAL CT. FAULT CURRENT MEASU..

Brand: LOVATO ELECTRIC | Manufacturer Part Number: R4D415



Manufacturer	LOVATO ELECTRIC
MPN / Reference	R4D415
Catalog number	10000
Category	Residual current monitoring relay
Minimum order	1 Pcs
Document ID	EO-1FA58DD2B2
Generated	2026-08-04

Product Overview

EARTH LEAKAGE RELAY WITH 2 OPERATION THRESHOLDS, FLUSH MOUNT. EXTERNAL CT. FAULT CURRENT MEASUREMENT. DIGITAL DISPLAY. FAIL SAFE. FLAG INDICATOR, 110VAC/DC-240VAC-415VAC

EARTH LEAKAGE RELAY R4D 110 - 240 - 415

Earth leakage relay with 2 operatin thresholds, flush-mount. External CT. Fault current measurement. Digital display. Fail safe. Flag indicator, 110VAC-240VAC-415VAC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	LOVATO ELECTRIC > Earth leakage relays - LOVATO ELECTRIC
--------------	--

Additional Product Information

R4D415

Earth leakage relay with 2 operatin thresholds, flush-mount. External CT. Fault current measurement. Digital display. Fail safe. Flag indicator, 110VAC-240VAC-415VAC

Technical specifications

Type of product:Earth leakage relaysResidual operation characteristic:Type AType of installation:Flush mountingToroidal transformer:ExternalN° of operating threshold:2Rated supply voltage:110...125/220...240/380...415VACOrder code

R4D415

Weight [g] 630

Qty. per package 1

Multiple qty. of packs per order 1
Package dimensions [mm] 115X160X115
Volume [cm³] 2116
Bar code [EAN13] 8013975111185
HS Code 85365080
670.01 £
ETIM for R4D415 Relays (EC001445)
Feature Name
Feature Value
Type of electric connection (EF003961)
Screw connection
Function (EF000030)
For AC-current system
Response value amperage 2 (EF008205)
21 mA
Response value amperage 1 (EF008204)
30 mA
Indication of difference current (EF003424)
Yes
Error registration possible (EF003423)
Yes
With detachable clamps (EF003340)
No
Number of contacts as change-over contact (EF008257)
2
Number of contacts as normally open contact (EF008256)
0
Number of contacts as normally closed contact (EF008255)
0
Min. adjustable delay-on energization time (EF008190)
0.03 s
Max. permitted delay-on energization time (EF008189)
5 s
Depth (EF000049)
120 mm
Height (EF000040)
96 mm
Width (EF000008)
96 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / R4D415 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.