

INDUSTRIAL COMPONENT DATA

M0P00910024 LOVATO direct starter without relay box with pushbutton start and stop / reset 9A 24V AC

Brand: LOVATO ELECTRIC | Manufacturer Part Number: M0P00910024



Manufacturer	LOVATO ELECTRIC
MPN / Reference	M0P00910024
Catalog number	10000
Category	Motor starter/Motor starter combination
Minimum order	1 Pcs
Document ID	EO-D4A1A5AF9D
Generated	2026-08-01

Product Overview

direct starter without relay box with pushbutton start and stop / reset 9A 24V AC

DOL STARTER M0P 24/50-60 W/O RELAY

Direct-on-line-starter, enclosed without thermal overload relay, with START and STOP/RESET buttons, with BG09/BG12 contactor, 12A max ($\leq 440V$), IP65. Contactor coil voltage 24VAC 50/60Hz

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LOVATO ELECTRIC > Electromechanical starters - LOVATO ELECTRIC

Additional Product Information

M0P00910024

Direct-on-line-starter, enclosed without thermal overload relay, with START and STOP/RESET buttons, with BG09/BG12 contactor, 12A max ($\leq 440V$), IP65. Contactor coil voltage 24VAC 50/60Hz

Technical specifications

Type of product:Direct-on-line-startersUL/CSA horsepower ratings 480V [HP]:5Type:Enclosed without thermal overload relayType of coil:AC coilOrder code M0P00910024

Weight [g] 668

Qty. per package 1

Multiple qty. of packs per order 1

Package dimensions [mm] 187X092X160

Volume [cm³] 2752.64

Bar code [EAN13] 8013975213735

HS Code 85371098
ETIM for M0P00910024 Low-voltage industrial controls and switchgear (EC001037)
Feature Name
Feature Value
Degree of protection (NEMA) (EF011959)
4X
Type of motor starter (EF009598)
Direct starter
Voltage type for actuating (EF008242)
AC
Type of electrical connection for auxiliary- and control current circuit (EF006979)
Screw connection
Type of electrical connection of main circuit (EF006819)
Screw connection
Release class (EF006668)
CLASS 10 A
Degree of protection (IP) (EF005474)
IP65
Rated control supply voltage AC 60 Hz (EF003979)
24 V
Rated control supply voltage AC 50 Hz (EF003978)
24 V
Temperature compensated overload protection (EF009604)
Yes
Supporting protocol for SafetyBUS p (EF007527)
No
Supporting protocol for PROFIsafe (EF007526)
No
Supporting protocol for PROFINET IO (EF007525)
No
Supporting protocol for PROFINET CBA (EF007524)
No
Supporting protocol for Foundation Fieldbus (EF007522)
No
Supporting protocol for E...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / M0P00910024 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.