

INDUSTRIAL COMPONENT DATA

GE2000E LOVATO 3P CHANGEOVER SWITCH AC21A 2000A

Brand: LOVATO ELECTRIC | Manufacturer Part Number: GE2000E



Manufacturer	LOVATO ELECTRIC
MPN / Reference	GE2000E
Catalog number	10000
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-0F29ED1766
Generated	2026-07-29

Product Overview

3P CHANGEOVER SWITCH AC21A 2000A

Three-pole changeover switch, 2000A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **LOVATO ELECTRIC > Switch disconnectors - LOVATO ELECTRIC**

Additional Product Information

GE2000E

Three-pole changeover switch, 2000A

Technical specifications

Type of product:Changeover switchesNumber of poles:3Type of operating voltage:ACIEC Conventional free air thermal current Ith [A]:2000Type of installation:Screw on plateOrder code GE2000E

Weight [g] 47000

Qty. per package 1

Multiple qty. of packs per order 1

Package dimensions [mm] 660X590X540

Volume [cm³] 210276

Bar code [EAN13] 8013975245811

HS Code 85365080

ETIM for GE2000E Low-voltage industrial controls and switchgear (EC000216)

Feature Name

Feature Value

Device construction (EF008240)
Built-in device fixed built-in technique
Type of control element (EF006976)
Door coupling rotary drive
Type of electrical connection of main circuit (EF006819)
Bolt connection
Rated operating voltage (EF001435)
400 V
Version as reversing switch (EF009408)
No
Voltage release optional (EF007491)
No
Motor drive optional (EF007386)
No
Suitable for distribution board installation (EF007262)
No
Suitable for front mounting 4-hole (EF007247)
No
Version as maintenance-/service switch (EF006986)
Yes
Version as safety switch (EF006985)
No
Version as main switch (EF006981)
Yes
Version as emergency stop installation (EF006959)
No
Motor drive integrated (EF006697)
No
Interlockable (EF006281)
No
Rated permanent current at AC-23, 400 V (EF011777)
1250 A
Rated permanent current at AC-21, 400 V (EF009165)
2000 A
Max. rated operation voltage Ue AC (EF007355)
690 V
Rated short-time withstand current Icw (EF007050)
50 kA
Rated operation powe...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / GE2000E with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.