

INDUSTRIAL COMPONENT DATA

GL0160C1 LOVATO Disconnecter three-pole bottom cabinet 160A AC21A C1

Brand: LOVATO ELECTRIC | Manufacturer Part Number: GL0160C1



Manufacturer	LOVATO ELECTRIC
MPN / Reference	GL0160C1
Catalog number	10000
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-19D2A361CE
Generated	2026-08-04

Product Overview

Disconnecter three-pole bottom cabinet 160A AC21A C1
3P SWITCH DISCONNECTOR 160A AC21A C1
Three-pole switch disconnecter, IEC/EN, 160A
THREE-POLE SWITCH DISCONNECTOR, IEC/EN, 160A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LOVATO ELECTRIC > Switch disconnectors - LOVATO ELECTRIC

Additional Product Information

GL0160C1

Three-pole switch disconnecter, IEC/EN, 160A

Technical specifications

Type of product: Switch disconnectors
Number of poles: 3
Type of operating voltage: AC
IEC Conventional free air thermal current I_{th} [A]: 160
Type of installation: Screw on plate or 35mm DIN rail
Order code GL0160C1

Weight [g] 1740

Qty. per package 1

Multiple qty. of packs per order 1

Package dimensions [mm] 160X168X105

Volume [cm³] 2822.4

Bar code [EAN13] 8013975228609

HS Code 85365080

136.42 £

ETIM for GL0160C1 Low-voltage industrial controls and switchgear (EC000216)

Feature Name

Feature Value

Device construction (EF008240)

Built-in device fixed built-in technique

Type of control element (EF006976)

Door coupling rotary drive

Type of electrical connection of main circuit (EF006819)

Bolt connection

Rated operating voltage (EF001435)

400 V

Version as reversing switch (EF009408)

No

Voltage release optional (EF007491)

No

Motor drive optional (EF007386)

No

Suitable for distribution board installation (EF007262)

No

Suitable for front mounting 4-hole (EF007247)

No

Version as maintenance-/service switch (EF006986)

Yes

Version as safety switch (EF006985)

No

Version as main switch (EF006981)

Yes

Version as emergency stop installation (EF006959)

No

Motor drive integrated (EF006697)

No

Interlockable (EF006281)

Yes

Rated permanent current at AC-23, 400 V (EF011777)

160 A

Rated permanent current at AC-21, 400 V (EF009165)

160 A

Max. rated operation voltage Ue AC (EF007355)

690 V

Rated short-time withstand current Icw (...)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / GL0160C1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.