

INDUSTRIAL COMPONENT DATA

GL0250C1 LOVATO Disconnecter three-pole bottom cabinet 250A AC21A C1

Brand: LOVATO ELECTRIC | Manufacturer Part Number: GL0250C1



Manufacturer	LOVATO ELECTRIC
MPN / Reference	GL0250C1
Catalog number	10000
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-DACA9F168D
Generated	2026-08-02

Product Overview

Disconnecter three-pole bottom cabinet 250A AC21A C1

3P SWITCH DISCONNECTOR 250A AC21A C1

Three-pole switch disconnecter, IEC/EN, 250A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LOVATO ELECTRIC > Switch disconnectors - LOVATO ELECTRIC

Additional Product Information

GL0250C1

Three-pole switch disconnecter, IEC/EN, 250A

Technical specifications

Type of product: Switch disconnectors
Number of poles: 3
Type of operating voltage: AC IEC Conventional
free air thermal current Ith [A]: 250
Type of installation: Screw on plate or 35mm DIN rail
Order code GL0250C1

Weight [g] 1740

Qty. per package 1

Multiple qty. of packs per order 1

Package dimensions [mm] 160X168X105

Volume [cm³] 2822.4

Bar code [EAN13] 8013975228623

HS Code 85365080

191.85 £

ETIM for GL0250C1 Low-voltage industrial controls and switchgear (EC000216)

Feature Name

Feature Value

Device construction (EF008240)

Built-in device fixed built-in technique

Type of control element (EF006976)

Door coupling rotary drive

Type of electrical connection of main circuit (EF006819)

Bolt connection

Rated operating voltage (EF001435)

400 V

Version as reversing switch (EF009408)

No

Voltage release optional (EF007491)

No

Motor drive optional (EF007386)

No

Suitable for distribution board installation (EF007262)

No

Suitable for front mounting 4-hole (EF007247)

No

Version as maintenance-/service switch (EF006986)

Yes

Version as safety switch (EF006985)

No

Version as main switch (EF006981)

Yes

Version as emergency stop installation (EF006959)

No

Motor drive integrated (EF006697)

No

Interlockable (EF006281)

No

Rated permanent current at AC-23, 400 V (EF011777)

250 A

Rated permanent current at AC-21, 400 V (EF009165)

250 A

Max. rated operation voltage Ue AC (EF007355)

690 V

Rated short-time withstand current Icw (E...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / GL0250C1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.