

INDUSTRIAL COMPONENT DATA

GL0315C1 LOVATO Disconnecter three-pole bottom closet 315A AC21A C1

Brand: LOVATO ELECTRIC | Manufacturer Part Number: GL0315C1



Manufacturer	LOVATO ELECTRIC
MPN / Reference	GL0315C1
Catalog number	10000
Category	Switch disconnector
Minimum order	1 Pcs
Document ID	EO-58FE1995F7
Generated	2026-08-02

Product Overview

Disconnecter three-pole bottom closet 315A AC21A C1

3P SWITCH DISCONNECTOR 315A AC21A C1

Three-pole switch disconnector, IEC/EN, 315A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LOVATO ELECTRIC > Switch disconnectors - LOVATO ELECTRIC

Additional Product Information

GL0315C1

Three-pole switch disconnector, IEC/EN, 315A

Technical specifications

Type of product:Switch disconnectorsNumber of poles:3Type of operating voltage:ACIEC Conventional free air thermal current Ith [A]:315Type of installation:Screw on plate or 35mm DIN railOrder code GL0315C1

Weight [g] 1740

Qty. per package 1

Multiple qty. of packs per order 1

Package dimensions [mm] 160X168X105

Volume [cm³] 2822.4

Bar code [EAN13] 8013975228630

HS Code 85365080

206.05 £

ETIM for GL0315C1 Low-voltage industrial controls and switchgear (EC000216)

Feature Name

Feature Value

Device construction (EF008240)

Built-in device fixed built-in technique

Type of control element (EF006976)

Door coupling rotary drive

Type of electrical connection of main circuit (EF006819)

Bolt connection

Rated operating voltage (EF001435)

400 V

Version as reversing switch (EF009408)

No

Voltage release optional (EF007491)

No

Motor drive optional (EF007386)

No

Suitable for distribution board installation (EF007262)

No

Suitable for front mounting 4-hole (EF007247)

No

Motor drive integrated (EF006697)

No

Interlockable (EF006281)

No

Rated permanent current at AC-23, 400 V (EF011777)

315 A

Rated permanent current at AC-21, 400 V (EF009165)

315 A

Max. rated operation voltage Ue AC (EF007355)

690 V

Rated short-time withstand current Icw (EF007050)

6 kA

Rated operation power at AC-23, 400 V (EF007027)

140 kW

Number of auxiliary contacts as change-over contact (EF003531)

0

Conditioned rated short-circuit current Iq (EF001...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / GL0315C1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.