

INDUSTRIAL COMPONENT DATA

GL0320C1 LOVATO Tripolar bottom disconnecter cabinet 320A AC21A C1

Brand: LOVATO ELECTRIC | Manufacturer Part Number: GL0320C1



Manufacturer	LOVATO ELECTRIC
MPN / Reference	GL0320C1
Catalog number	10000
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-90BBD9D99D
Generated	2026-08-04

Product Overview

Tripolar bottom disconnecter cabinet 320A AC21A C1
 Three-pole switch disconnecter, IEC/EN, 320A
 THREE-POLE SWITCH DISCONNECTOR, IEC/EN, 320A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LOVATO ELECTRIC > Switch disconnectors - LOVATO ELECTRIC

Additional Product Information

GL0320C1
 Three-pole switch disconnecter, IEC/EN, 320A
 Technical specifications
 Type of product:Switch disconnectorsNumber of poles:3Type of operating voltage:ACIEC Conventional free air thermal current Ith [A]:320Type of installation:Screw on plateOrder code GL0320C1
 Weight [g] 3456.4
 Qty. per package 1
 Multiple qty. of packs per order 1
 Package dimensions [mm] 233X197X115
 Volume [cm³] 5278
 Bar code [EAN13] 8013975245538
 HS Code 85365080
 224.54 £

ETIM for GL0320C1 Low-voltage industrial controls and switchgear (EC000216)

Feature Name

Feature Value

Device construction (EF008240)

Built-in device fixed built-in technique

Type of control element (EF006976)

Door coupling rotary drive

Type of electrical connection of main circuit (EF006819)

Bolt connection

Rated operating voltage (EF001435)

400 V

Version as reversing switch (EF009408)

No

Voltage release optional (EF007491)

No

Motor drive optional (EF007386)

No

Suitable for distribution board installation (EF007262)

No

Suitable for front mounting 4-hole (EF007247)

No

Version as maintenance-/service switch (EF006986)

Yes

Version as safety switch (EF006985)

No

Version as main switch (EF006981)

Yes

Version as emergency stop installation (EF006959)

No

Motor drive integrated (EF006697)

No

Interlockable (EF006281)

No

Rated permanent current at AC-23, 400 V (EF011777)

320 A

Rated permanent current at AC-21, 400 V (EF009165)

320 A

Max. rated operation voltage Ue AC (EF007355)

690 V

Rated short-time withstand current Icw (EF007050)

12.5 kA....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / GL0320C1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.