

INDUSTRIAL COMPONENT DATA

GL0400C1UL LOVATO Tripolar bottom disconnecter cabinet 400A AC21A C1 UL98

Brand: LOVATO ELECTRIC | Manufacturer Part Number: GL0400C1UL



Manufacturer	LOVATO ELECTRIC
MPN / Reference	GL0400C1UL
Catalog number	10000
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-11D69C7EB4
Generated	2026-08-01

Product Overview

Tripolar bottom disconnecter cabinet 400A AC21A C1 UL98

Three-pole switch disconnecter, UL98, 400A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LOVATO ELECTRIC > Switch disconnectors - LOVATO ELECTRIC

Additional Product Information

GL0400C1UL

Three-pole switch disconnecter, UL98, 400A

Technical specifications

Type of product: Switch disconnectors Number of poles: 3 Type of operating voltage: AC IEC Conventional free air thermal current Ith [A]: 400 UL Standard: UL98 Type of installation: Screw on plate Order code GL0400C1UL

Weight [g] 3777

Qty. per package 1

Multiple qty. of packs per order 1

Package dimensions [mm] 261X269X115

Volume [cm³] 8074

Bar code [EAN13] 8013975245576

HS Code 85365080

440.54 £

ETIM for GL0400C1UL Low-voltage industrial controls and switchgear (EC000216)

Feature Name

Feature Value

Device construction (EF008240)

Built-in device fixed built-in technique

Type of control element (EF006976)

Door coupling rotary drive

Type of electrical connection of main circuit (EF006819)

Bolt connection

Rated operating voltage (EF001435)

400 V

Version as reversing switch (EF009408)

No

Voltage release optional (EF007491)

No

Motor drive optional (EF007386)

No

Suitable for distribution board installation (EF007262)

No

Suitable for front mounting 4-hole (EF007247)

No

Version as maintenance-/service switch (EF006986)

Yes

Version as safety switch (EF006985)

No

Version as main switch (EF006981)

Yes

Version as emergency stop installation (EF006959)

No

Motor drive integrated (EF006697)

No

Interlockable (EF006281)

No

Rated permanent current at AC-21, 400 V (EF009165)

400 A

Max. rated operation voltage Ue AC (EF007355)

600 V

Rated short-time withstand current Icw (EF007050)

12.5 kA

Rated operation power at AC-23, 400 V (...)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / GL0400C1UL with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.