

INDUSTRIAL COMPONENT DATA

GL0500C1 LOVATO Tripolar bottom disconnecter cabinet 500A AC21A C1

Brand: LOVATO ELECTRIC | Manufacturer Part Number: GL0500C1



Manufacturer	LOVATO ELECTRIC
MPN / Reference	GL0500C1
Catalog number	10000
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-A9C7FD2607
Generated	2026-08-04

Product Overview

Tripolar bottom disconnecter cabinet 500A AC21A C1

Three-pole switch disconnecter, IEC/EN, 500A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LOVATO ELECTRIC > Switch disconnectors - LOVATO ELECTRIC

Additional Product Information

GL0500C1

Three-pole switch disconnecter, IEC/EN, 500A

Technical specifications

Type of product: Switch disconnectors Number of poles: 3 Type of operating voltage: AC IEC Conventional free air thermal current Ith [A]: 500 Type of installation: Screw on plate Order code GL0500C1

Weight [g] 3440

Qty. per package 1

Multiple qty. of packs per order 1

Package dimensions [mm] 233X197X115

Volume [cm³] 5278

Bar code [EAN13] 8013975245552

HS Code 85365080

284.21 £

ETIM for GL0500C1 Low-voltage industrial controls and switchgear (EC000216)

Feature Name
Feature Value
Device construction (EF008240)
Built-in device fixed built-in technique
Type of control element (EF006976)
Door coupling rotary drive
Type of electrical connection of main circuit (EF006819)
Bolt connection
Rated operating voltage (EF001435)
400 V
Version as reversing switch (EF009408)
No
Voltage release optional (EF007491)
No
Motor drive optional (EF007386)
No
Suitable for distribution board installation (EF007262)
No
Suitable for front mounting 4-hole (EF007247)
No
Version as maintenance-/service switch (EF006986)
Yes
Version as safety switch (EF006985)
No
Version as main switch (EF006981)
Yes
Version as emergency stop installation (EF006959)
No
Motor drive integrated (EF006697)
No
Interlockable (EF006281)
No
Rated permanent current at AC-23, 400 V (EF011777)
500 A
Rated permanent current at AC-21, 400 V (EF009165)
500 A
Max. rated operation voltage Ue AC (EF007355)
690 V
Rated short-time withstand current Icw (EF007050)
12.5 kA
Ra...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / GL0500C1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.