

INDUSTRIAL COMPONENT DATA

GLC0320C1 LOVATO Tetrapolar switch back cabinet 160A AC21A C1

Brand: LOVATO ELECTRIC | Manufacturer Part Number: GLC0320C1



Manufacturer	LOVATO ELECTRIC
MPN / Reference	GLC0320C1
Catalog number	10000
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-EAAC4631AE
Generated	2026-08-04

Product Overview

Tetrapolar switch back cabinet 160A AC21A C1

Three-pole changeover switch, IEC/EN, 320A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LOVATO ELECTRIC > Switch disconnectors - LOVATO ELECTRIC

Additional Product Information

GLC0320C1

Three-pole changeover switch, IEC/EN, 320A

Technical specifications

Type of product:Changeover switchesNumber of poles:3Type of operating voltage:ACIEC Conventional free air thermal current Ith [A]:320Type of installation:Screw on plateOrder code GLC0320C1

Weight [g] 7180

Qty. per package 1

Multiple qty. of packs per order 1

Package dimensions [mm] 290X200X250

Volume [cm³] 14500

Bar code [EAN13] 8013975267097

HS Code 85365080

675.03 £

ETIM for GLC0320C1 Low-voltage industrial controls and switchgear (EC000216)

Feature Name
Feature Value
Device construction (EF008240)
Built-in device fixed built-in technique
Type of control element (EF006976)
Door coupling rotary drive
Type of electrical connection of main circuit (EF006819)
Bolt connection
Rated operating voltage (EF001435)
400 V
Version as reversing switch (EF009408)
No
Voltage release optional (EF007491)
No
Motor drive optional (EF007386)
No
Suitable for distribution board installation (EF007262)
No
Suitable for front mounting 4-hole (EF007247)
No
Version as maintenance-/service switch (EF006986)
Yes
Version as safety switch (EF006985)
No
Version as main switch (EF006981)
Yes
Version as emergency stop installation (EF006959)
No
Motor drive integrated (EF006697)
No
Interlockable (EF006281)
No
Rated permanent current at AC-23, 400 V (EF011777)
320 A
Rated permanent current at AC-21, 400 V (EF009165)
320 A
Max. rated operation voltage Ue AC (EF007355)
690 V
Rated short-time withstand current Icw (EF007050)
12.5 kA
R...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LOVATO ELECTRIC / GLC0320C1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.